



**The article is no longer in our assortment.**

### Features:

#### EUROLITE LED PAR-56 RGB 5mm Short 5CH sil

PAR-56 spot with 151 LEDs in the colors red, green and blue

- Equipped with 151 x 5 mm LED: 51 x red, 49 x green, 51 x blue
- Operable in stand-alone mode or with DMX interface
- DMX-512 control possible via any commercial DMX-controller (occupies 5 channels)
- 3 or 5 DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Adjustable microphone sensitivity via LED display
- Comfortable addressing and setting via control panel with LED display and three operating buttons
- Functions: static colors; RGB color blend, internal programs, dimmer and strobe settings via DMX; master/slave
- Housing available in silver or in black
- Locking possibility at the mounting bracket
- Ready for connection with power cord and safety plug
- 151 powerful LEDs 5 mm R/G/B (homogenous color mix)
- Strobe effect
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512
- With a beam angle of 21°

### Logistic

#### ROADINGER Flightcase EPS-56 4x PAR-56 Spot short

Trunk case

- With 4 device compartments

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

Weight:	13,75 kg
---------	----------

### EUROLITE LED PAR-56 RGB 5mm Short 5CH sil

Power supply:	230 V AC, 50 Hz
Power consumption:	23 W
IP classification:	IP20
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED type:	151 x 5 mm R/G/B (homogenous color mix)
DMX channels:	5; 3
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	Light J; LED PC-Control 512
Beam angle:	21°
Beam angle (1/2 peak):	21°
Housing color:	Silver
Dimensions:	Width: 20,5 cm Depth: 16,5 cm Height: 24 cm
Weight:	1,45 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### ROADINGER Flightcase EPS-56 4x PAR-56 Spot short

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated

Compartment dimensions:	22 cm x 22 cm x 24 cm
Inside dimensions:	44 cm x 44 cm x 24 cm
Dimensions:	Width: 48,5 cm Depth: 48,5 cm Height: 31 cm
Weight:	7,95 kg