# EUROLITE Set 4x AKKU UP-4 QCL Spot QuickDMX + SB-4 Soft Bag

**Art. No.: 20000031**

GTIN:

## The article is no longer in our assortment.

### Features:

**EUROLITE AKKU UP-4 QCL Spot QuickDMX**

Bright Uplight with 4 x 8 W 4in1 LED and QuickDMX transceiver

- Integrated QuickDMX transceiver for wireless DMX control
- Battery operation up to 9,5h depending on program used
- 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone
- Flicker-free
- With a beam angle of 22°
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Dimmer speed (step response) adjustable; Dimmer electronic; color blend stepless; color change adjustable
- Strobe effect
- Preprogrammed in Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- Mains input and output for power linking up to 8 units
- Integrated automatic charging of the battery and status indicator
- With bracket for floor use
- Cordless, flexible and versatile
- Silent operation
- Application possibility: Standing

**Package contents**

- 1 x spotlight, 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x remote control, 1 x battery

### Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

**EUROLITE SB-4 Soft Bag M**

Black soft bag for up to four devices (Akku UP-4/TL-3 TCL)

- Practical transport bag offers enough space for several lighting effects and accessories
- Large interior, four times divisible and adaptable with foam dividers and pads
- Suitable e.g. for 4 x AKKU UP-4 Spot, 4 x TL-3 TCL Trusslight (41700500) or 3 x AKKU UP-4 Spot QuickDMX (41700540)
- Interior upholstery helps securing and safeguarding the fixtures during transportation
- External pocket stores accessories like cables, clamps, lamps and tape
- Made of easy-care nylon
- Carrying handles

## Technical specifications:

| | |
|---|---|
| Weight: | 14,87 kg |

**EUROLITE AKKU UP-4 QCL Spot QuickDMX**

| | |
|---|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 50 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Battery/battery pack<br>Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Cable length: | Approx. 1 m |
| Power output: | 1 x P-Con (gray), mounting version |
| Battery pack type: | 1 x lithium ion 14,8 V, 7800 mAh, 115,44 Wh |
| Battery pack: | Battery operation up to 9,5h depending on program used<br>Recharging time 3h |
| Lamp type: | LED lamp |
| LED: | 4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) |
| DMX channels: | 3; 4; 6; 8; 10 |
| DMX input: | 1 x 3-pin XLR (M) mounting version IP |
| DMX output: | 1 x 3-pin XLR (F) mounting version IP |
| Cooling: | Passive convection cooling |
| Control: | DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone |
| Preprogrammed in: | Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain |
| Projection: | Flicker-free |
| Carrier frequency: | 2,4 GHz |
| Beam angle: | 22° |
| Beam angle (1/2 peak): | 22° |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| | |
|---|---|
| Beam angle (1/10 peak): | 32° |
| Housing color: | Black |
| Attachment system: | Bracket for floor use |
| Dimensions: | Width: 16,7 cm<br>Depth: 13,8 cm<br>Height: 18,8 cm |
| Weight: | 3,59 kg |
| Noise classification: | Class 0 (no noise at all) |
| Remote control | |
| Battery: | 1 x  Button cell 3.0 V CR2032 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

**EUROLITE SB-4 Soft Bag M**

| | |
|---|---|
| Maximum load: | 25 kg |
| Material: | Textile |
| Color: | Black |
| Compartment dimensions: | 14 cm x 14 cm x 19 cm |
| Inside dimensions: | 29 cm x 29 cm x 19 cm |
| Dimensions: | Width: 30 cm<br>Depth: 33 cm<br>Height: 20 cm |
| Weight: | 510 g |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.