

EUROLITE Set LED PFE-50 + Lens Tube 36° + DMX Interface

Handy stage spotlight including lens tube and control modul with DMX interface

Art. No.: 2000058

GTIN:



Features:

- Silent operation
- <p>EUROLITE LED PFE-50 3000K Profile Spot
- <h2 class="featureSatz">Handy stage spotlight with 50 W COB LED in modular construction system, CRI >80</h2>Modular construction kit that can be customized to individual preferences
- 4 shutter blades
- Dimmer and strobe, master/slave functions adjustable via optional DMX interface
- Dimmable
- 1 LED 50 W COB (chip-on-board) warm white (WW)
- The device is cooled by cooling fan
- Control via on/off switch on device; master/slave function
- Fixtures available for LED PC-Control 512; Light Captain; Light`J
- Flicker-free
- With a beam angle of 19°
- Very high color rendering index (CRI)
- With mounting bracket
- Very quiet working noise
- For application areas such as: Trade fair and shop fitting; installation; theater; rental
- Application possibility: Suspended; on stand
- <p>EUROLITE Lens Tube 36° for LED PFE-50
- <h2 class="featureSatz">Lens tube for EUROLITE LED PFE-50 3000 K Profile Spot</h2>Lens tube available with a beam angle of 19°, 26°, 36° or 50°
- With a beam angle of 36°
- <p>EUROLITE DMX-Interface for LED PFE-50
- <h2 class="featureSatz">Control unit with DMX interface for EUROLITE LED PFE-50 3000 K Profile Spot</h2>Adds full DMX functionality to the spotlight
- Dimmer electronic

Logistic

- Strobe effect
- Control via DMX; master/slave function
- 4 digit 7-segment LED display

Technical specifications:

Weight:	2.32 kg
Noise classification:	Class 0 (no noise at all)

EUROLITE LED PFE-50 3000K Profile Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	55 W
IP classification:	IP20
Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
Lamp specification:	Dimmable
LED type:	1 x 50 W COB (chip-on-board) warm white (WW)
Cooling:	Cooling fan
Control:	On/off switch on device; master/slave function
Fixtures available for:	LED PC-Control 512; Light Captain; Light J
Projection:	Flicker-free
Beam angle (1/2 peak):	19° (optional) 26° (optional) 36° (optional) 50° (optional)
Color temperature:	3000K
Color rendering index (CRI):	91 Ra
Illuminance in Lux (lx):	Warm white (WW) 1m: 0 lx, 3m: 1669 lx, 6m: 432 lx
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 30.5 cm Width: 13.4 cm Height: 23.8 cm
Weight:	1.97 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE Lens Tube 36° for LED PFE-50

Beam angle (1/2 peak):	36°
------------------------	-----

Weight: 0.23 kg

EUROLITE DMX-Interface for LED PFE-50

IP classification: IP20

DMX channels: 2

Control: DMX; master/slave function

Housing color: Black

Display type: 4 digit 7-segment LED display

Dimensions: Width: 7.1 cm
Depth: 3.7 cm
Height: 6.4 cm

Weight: 0.12 kg

Scope of delivery:

1 x EUROLITE LED PFE-50 3000K Profile Spot

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x filter frame
- 1 x gobo holder
- 1 x terminating plug (power)

1 x EUROLITE DMX-Interface for LED PFE-50

- 1 x device
- 1 x USB cable
- 4 x screw