eurolite®

EUROLITE Set PAR-16 Spot wh + GU-10 230V COB 1x3W LED 2700K

PAR-16 housing with GU-10 socket including special lamp for show effect lighting

Art. No.: 20000097







The article is no longer in our assortment.

Features:

EUROLITE PAR-16 Spot GU-10 white

PAR-16 housing with GU10 socket (with plug + cable)

- Mini-spot for GU-10 lamp
- Color-filters attachable
- Control via plug and play

For PAR 16
Package contents

- 1 x spotlight, 1 x filter frame, 1 x user manual

OMNILUX GU-10 230V COB 1x3W LED 2700K

Special lamp for show effect lighting

- Hot restrike

Technical specifications:

Weight:

0,35 kg

EUROLITE PAR-16 Spot GU-10 white

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 75 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0,75 mm ² H05SS-F
Cable length:	Approx. 0,4 m
Base:	GU10
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-16
Housing color:	White
Material:	Aluminum, 1 mm
Slot for spot length:	7,8 cm x 7,8 cm
Dimensions:	Length: 17 cm
	Width: 11 cm
	Height: 13 cm
Weight:	0,30 kg
Mounting bracket	
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Filter frame	
Shape:	Octagonal
Material:	Aluminum
Color:	White
Dimensions:	Length: 7,7 cm
	Width: 7,7 cm
	Diameter: Ø 5,3 cm
Weight:	0,01 kg

OMNILUX GU-10 230V COB 1x3W LED 2700K

Voltage (lamps):	230 V, AC
Nominal wattage:	3 W
Base:	GU10
Lamp type:	LED lamp; clear lamp; high voltage lamp
Lamp specification:	Hot restrike
Beam angle:	38°
Color of light:	White
Color temperature:	2700K
Lead time:	1 s
Construction:	Reflector; bi pin
Operating temperature max.:	40° C
Operating temperature min.:	20° C

Burning position:	S180 (universal)
Lamp life:	50000 h
Lamp current:	0,028 A
Dimensions (LxD):	60x51 mm
Weight:	0,05 kg
Legal specifications	
Energy efficiency class (A++ - E):	Α