



The article is no longer in our assortment.

Features:

EUROLITE PAR-16 Spot GU-10 white

PAR-16 housing with GU10 socket (with plug + cable)

- Mini-spot for GU-10 lamp
- Color-filters attachable
- Control via plug and play
- For PAR 16

Package contents

- 1 x spotlight, 1 x filter frame, 1 x user manual

Logistic

OMNILUX GU-10 230V COB 1x3W LED 6000K

Special lamp for show effect lighting

- Spare lamp for Eurolite PAR-16 spots: 50850340 EUROLITE PAR-16 Spot GU-10 silver, 50850350 EUROLITE PAR-16 Spot GU-10 black, 50850352 EUROLITE PAR-16 Spot GU-10 white
- Hot restrike

Technical specifications:

Weight:

0,33 kg

EUROLITE PAR-16 Spot GU-10 white

| | |
|--------------------------|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | Max. 75 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Cable construction: | 3 x 0,75 mm² H05SS-F |
| Cable length: | Approx. 0,4 m |
| Base: | GU10 |
| Lamp type: | Selectable |
| Color generation: | Via color filter frame |
| Control: | Plug and play |
| Construction: | PAR-16 |
| Housing color: | White |
| Material: | Aluminum, 1 mm |
| Slot for spot length: | 7,8 cm x 7,8 cm |
| Dimensions: | Length: 17 cm Width: 11 cm Height: 13 cm |
| Weight: | 0,30 kg |
| Mounting bracket | |
| Diameter mounting holes: | 2 x Ø10mm |
| Material: | Aluminum, 3 mm |
| Filter frame | |
| Shape: | Octagonal |
| Material: | Aluminum |
| Color: | White |
| Dimensions: | Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,3 cm |
| Weight: | 0,01 kg |

OMNILUX GU-10 230V COB 1x3W LED 6000K

| | |
|---------------------|---|
| Voltage (lamps): | 230 V, AC |
| Nominal wattage: | 3 W |
| Base: | GU10 |
| Lamp type: | LED lamp; clear lamp; high voltage lamp |
| Lamp specification: | Hot restrike |
| Beam angle: | 38° |
| Color of light: | White |
| Color temperature: | 6000K |
| Lead time: | 1 s |

| | |
|------------------------------------|-------------------|
| Construction: | Reflector; bi pin |
| Operating temperature max.: | 40° C |
| Operating temperature min.: | 20° C |
| Burning position: | S180 (universal) |
| Lamp life: | 50000 h |
| Lamp current: | 0,028 A |
| Dimensions (LxD): | 60x51 mm |
| Legal specifications | |
| Energy efficiency class (A++ - E): | A |