



Features:

EUROLITE PAR-16 Spot GU-10 white

PAR-16 housing with GU10 socket (with plug + cable)

- Mini-spot for GU-10 lamp
- Color-filters attachable
- Control via plug and play
- For PAR 16
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation

OMNILUX GU-10 230V COB 1x3W LED 6000K

Special lamp for show effect lighting

- Spare lamp for Eurolite PAR-16 spots: 50850340 EUROLITE PAR-16 Spot GU-10 silver, 50850350 EUROLITE PAR-16 Spot GU-10 black, 50850352 EUROLITE PAR-16 Spot GU-10 white
- Hot restrike

Technical specifications:

Weight:

0.33 kg

Logistic

EUROLITE PAR-16 Spot GU-10 white

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 75 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0.75 mm ² H05SS-F
Cable length:	Approx. 0.4 m
Base:	GU10
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-16
Housing color:	White
Material:	Aluminum, 1 mm
Slot for spot length:	7.8 cm x 7.8 cm
Dimensions:	Length: 17 cm Width: 11 cm Height: 13 cm
Weight:	0.30 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Shape:	Octagonal
Material:	Aluminum
Color:	White
Dimensions:	Length: 7.7 cm Width: 7.7 cm Diameter: Ø 5.3 cm
Weight:	0.01 kg

OMNILUX GU-10 230V COB 1x3W LED 6000K

Voltage (lamps):	230 V, AC
Nominal wattage:	3 W
Base:	GU10
Lamp type:	LED lamp; clear lamp; high voltage lamp
Lamp specification:	Hot restrike
Beam angle:	38°
Color of light:	White
Color temperature:	6000K
Lead time:	1 s
Construction:	Reflector; bi pin

Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	50000 h
Lamp current:	0.028 A
Dimensions (LxD):	60x51 mm
Energy efficiency class (A++ - E):	A

Scope of delivery:

- 1 x spotlight
- 1 x filter frame
- 1 x user manual