

# EUROLITE Set PAR-16 Spot sil + GU-10 230V COB 1x3W LED 6000K

Art. No.: 20000101

GTIN:









# The article is no longer in our assortment.

Features:	Logistic

# **EUROLITE PAR-16 Spot GU-10 silver**

PAR-16 housing with GU10 socket (with plug + cable)

- Mini-spot for GU-10 lamp
- Control via plug and play
- For PAR 16

#### Package contents

- 1 x spotlight, 1 x filter frame, 1 x user manual

#### **OMNILUX GU-10 230V COB 1x3W LED 6000K**

Special lamp for show effect lighting

- Spare lamp for Eurolite PAR-16 spots: 50850340 EUROLITE PAR-16 Spot GU-10 silver, 50850350 EUROLITE PAR-16 Spot GU-10 black, 50850352 EUROLITE PAR-16 Spot GU-10 white
- Hot restrike

Technical specifications:			
Weight:	0,30 kg		

# **EUROLITE PAR-16 Spot GU-10 silver**

Power supply:	230 V AC, 50 Hz	
Power consumption:	Max. 75 W	
IP classification:	IP20	
Protection class:	Protection class I	
Power connection:	Fixed power supply cord with safety plug	
Cable construction:	3 x 0,75 mm² H05SS-F	
Cable length:	Approx. 0,4 m	
Base:	GU10	
Lamp type:	Selectable	
Color generation:	Via color filter frame	
Control:	Plug and play	
Construction:	PAR-16	
Housing color:	Silver	
Material:	Aluminum, 1 mm	
Slot for spot length:	8 cm x 8 cm	
Dimensions:	Length: 17 cm	
	Width: 11 cm	
	Height: 13 cm	
Weight:	0,28 kg	
Mounting bracket		
Diameter mounting holes:	2 x Ø10mm	
Material:	Aluminum, 3 mm	
Filter frame		
Shape:	Octagonal	
Material:	Aluminum	
Dimensions:	Length: 7,7 cm	
	Width: 7,7 cm	
	Diameter: Ø 5,3 cm	
Weight:	0,01 kg	

# **OMNILUX GU-10 230V COB 1x3W LED 6000K**

Voltage (lamps):	230 V, AC
Nominal wattage:	3 W
Base:	GU10
Lamp type:	LED lamp; clear lamp; high voltage lamp
Lamp specification:	Hot restrike
Beam angle:	38°
Color of light:	White
Color temperature:	6000K
Lead time:	1 s
Construction:	Reflector; bi pin

Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	50000 h
Lamp current:	0,028 A
Dimensions (LxD):	60x51 mm
Legal specifications	
Energy efficiency class (A++ - E):	A