

EUROLITE Set PAR-16 Spot bk + GU-10 230V COB 7W 6400K

PAR-16 housing with GU-10 socket including special lamp for show effect lighting

Art. No.: 20000105

GTIN:



The article is no longer in our assortment.

Features:

EUROLITE PAR-16 Spot GU-10 black

PAR-16 housing with GU10 socket (with plug + cable)

- Mini-spot for GU-10 lamp
- Color-filters attachable
- Control via plug and play
- For PAR 16

Package contents

- 1 x spotlight, 1 x filter frame, 1 x user manual

Logistic

OMNILUX GU-10 230V COB 7W 6400K

Special lamp for show effect lighting

- Spare lamp for Eurolite PAR-16 spots: 50850340 EUROLITE PAR-16 Spot GU-10 silver, 50850350 EUROLITE PAR-16 Spot GU-10 black, 50850352 EUROLITE PAR-16 Spot GU-10 white
- Hot restrike
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 0,32 kg

EUROLITE PAR-16 Spot GU-10 black

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 75 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0,75 mm² H05SS-F
Cable length:	Approx. 0,4 m
Base:	GU10
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-16
Housing color:	Black
Material:	Aluminum, 1 mm
Slot for spot length:	7,8 cm x 7,8 cm
Dimensions:	Length: 17 cm Width: 11 cm Height: 13 cm
Weight:	0,28 kg
Mounting bracket	
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Filter frame	
Shape:	Octagonal
Material:	Aluminum, 0,5 mm
Dimensions:	Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,2 cm
Weight:	0,01 kg

OMNILUX GU-10 230V COB 7W 6400K

Voltage (lamps):	230 V, AC
Nominal wattage:	7 W
Base:	GU10
Lamp type:	LED lamp; clear lamp; high voltage lamp
Lamp specification:	Hot restrike
Beam angle:	90°
Color of light:	White
Color temperature:	6400K
Lead time:	1 s
Construction:	Reflector; bi pin

Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	30000 h
Luminous flux:	550 lm
Lamp current:	0,06 A
Dimensions (LxD):	72x51 mm
Weight:	0,04 kg
Legal specifications	
Energy efficiency class (A++ - E):	A+