eurolite®

EUROLITE Set PAR-38 Spot bk + PAR-38 230V SMD 15W LED 2700K

Art. No.: 20000108 GTIN:







The article is no longer in our assortment.

Features:

EUROLITE PAR-38 Spot bk

PAR-38 housing with E27 socket (with plug + cable)

- Heat-resistant fixing screw
- Precise light output
- Strong cable tension relief
- Control via plug and play
- With mounting bracket
- For PAR 38
- Package contents
- 1 x spotlight, 1 x filter frame, 1 x user manual

OMNILUX PAR-38 230V SMD 15W E-27 LED 2700K

PAR-38 lamp

- Easy installation
- Good color rendering index (CRI)
- For application areas such as: Clubs/dancing school; stage
- Package contents
- 1 x illuminant

Technical specifications:

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo. EUROLITE PAR-38 Spot bk

| EUROLITE PAR-36 Spot DK | |
|--------------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | Max. 85 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Cable construction: | 3 x 0,75 mm² H05SS-F |
| Cable length: | Approx. 0,9 m |
| Base: | E27 |
| Lamp type: | Selectable |
| Color generation: | Via color filter frame |
| Control: | Plug and play |
| Construction: | PAR-38 |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Material: | Aluminum; metal |
| Slot for spot length: | 17,2 cm x 17,2 cm |
| Dimensions: | Width: 19 cm |
| | Depth: 19 cm |
| | Height: 21,5 cm |
| Weight: | 0,70 kg |
| Mounting bracket | |
| Diameter mounting holes: | 2 x Ø12mm |
| Material: | Metal, 2 mm |
| Filter frame | |
| Diameter mounting holes: | 2 x Ø8mm |
| Material: | Metal |
| Dimensions: | Length: 17 cm |
| | Width: 17 cm |
| | Diameter: Ø 14 cm |
| Weight: | 0,12 kg |

OMNILUX PAR-38 230V SMD 15W E-27 LED 2700K

| Operating voltage: | 230 |
|--------------------|--------------------------|
| Nominal wattage: | 15 W |
| Base: | E27 |
| Lamp type: | LED lamp; reflector lamp |
| Beam angle: | 60° |
| Setup: | Easy installation |
| Color of light: | White |
| Color temperature: | 2700K |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| Color rendering index (CRI): | 81 Ra |
|----------------------------------|------------------|
| Lead time: | 0,2 s |
| Construction: | PAR-38 |
| Operating temperature max.: | 40° C |
| Operating temperature min.: | 20° C |
| Burning position: | S180 (universal) |
| Lamp life: | 20000 h |
| Luminous flux: | 1250 lm |
| Wavelength: | 608 nm |
| Lamp current: | 0,155 A |
| Dimensions (LxD): | 135x121 mm |
| Weight: | 0,36 kg |
| Energy efficiency class (A - G): | F |
| EPREL-Nr: | 1042577 |