



Features:

EUROLITE LED TMH FE-300 Beam/Flower Effect

Handy RGBW moving head flower with rotating lens and 12 W LEDs

- Equipped with 3 x 12 W COB LED in the colors red, green, blue and white
- 11 or 17 DMX channels selectable
- Compact lightweight
- Functions: colored beams in R, G, B and W, color change with diverse settings, built-in program, strobe effect with variable speed, dimmer, sound-control, Master/Slave operation
- Adjustable zoom movement - from narrow single beam to room-filling beams - via rotating lens
- Stepless RGBW color mixture
- Strobe effect with 1-18 flashes per second
- Exact positioning via 16 bit PAN/TILT movement resolution
- Positioning within 540° PAN and 190° TILT
- Automatic position correction
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Control board with 4-digit LED display for adjusting the DMX-starting address, PAN/TILT reverse, program, reset
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection with power cord and safety plug
- DMX control via every standard DMX controller
- 3 LEDs 12 W COB (chip-on-board) 4in1 RGBW
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Multi beam effect; beam effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone
- Flicker-free

Logistic

- With a beam angle of 6.5°

ROADINGER Flightcase 4x TMH-14/FE-300

Trunk case, PRO version

- With 4 device compartments
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	27.71 kg
---------	----------

EUROLITE LED TMH FE-300 Beam/Flower Effect

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	3 x 12 W COB (chip-on-board) 4in1 RGBW
Max. TILT movement:	190° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1 - 18 Hz
DMX channels:	11; 17
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone
Fixtures available for:	Light J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle (1/2 peak):	6.5°
Housing color:	Black
Dimensions:	Width: 20 cm Depth: 14.5 cm Height: 28 cm
Weight:	3.93 kg
Special product:	Not designed for household room illumination

Intended use: Show effect lighting

ROADINGER Flightcase 4x TMH-14/FE-300

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Middle compartment:	9.5 cm x 38 cm x 27 cm
Device compartment:	16 cm x 15 cm x 21 cm
Inside dimensions:	57.5 cm x 38 cm x 27 cm
Dimensions:	Width: 63 cm Depth: 45 cm Height: 37 cm
Weight:	12.00 kg

Scope of delivery:

1 x omega bracket