



Features:

EUROLITE TMH XB-200 Moving Head Beam

High performance beam for 200 W discharge lamp

- Very narrow beam angle with 2°
- With electronic ballast
- Color wheel with 13 different dichroic color filters plus white
- Switchable color change (mode 1: only full colors, mode 2: half colors)
- Rainbow effect with adjustable speed
- 8-facet prism
- Frost-filter
- Gobo wheel with 13 static gobos plus open
- With gobo shake function
- Motorized focus
- Strobe effect with adjustable speed
- Random strobe effect
- Dimmer
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- Switch-mode power supply for operation between 100 and 240 volts
- Control board with graphic LC display and encoder for adjusting the DMX-starting address, PAN/TILT reverse, reset, lamp on/off, operating hours
- DMX-controlled operation or stand-alone operation with master/slave function
- For OSD 5 Reflector 200 W discharge lamp
- Power connection via Neutrik PowerCon socket and included power cable
- DMX-control via every standard DMX-controller

Logistic

OMNILUX OSD 5 Reflector 200W Discharge Lamp

OMNILUX OSD technology

- Very short arc
- Compact design
- Reflector lamp
- Long life
- High beam intensity
- Freedom to create smaller and lighter fixtures
- Perfect alignment and placing with lamp replacements in seconds
- Renewed optical system with maximum light output
- High perceived brightness
- Dimmable
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 12.87 kg

EUROLITE TMH XB-200 Moving Head Beam

Power supply: 100-240 V AC, 50/60 Hz

Fixtures available for: LED PC-Control 512

Dimensions: Width: 31 cm
Depth: 25 cm
Height: 38 cm

Power consumption: 250 W

DMX channels: 16

DMX connection: 3-pin XLR

Flash-rate: 1-10 Hz

Color-wheel: 13 dichroic filters plus open

Static gobo-wheel: 13 gobos and open

Maximum PAN-movement: 540°

Maximum TILT-movement: 270°

Beam angle: 2°

Dimensions (L x W x H): 250 x 310 x 380 mm

Weight: 12 kg

Special product: Not designed for household room illumination

Intended use: Show effect lighting

OMNILUX OSD 5 Reflector 200W Discharge Lamp

Operating voltage: 75

Nominal wattage: 200 W

Base: Special

Lamp type: Discharge lamp

Lamp specification:	Dimmable
Color temperature:	8200K
Burning position:	S180 (universal)
Lamp life:	2000 h
Luminous flux:	8500 lm
Lamp current:	2.7 A
Dimensions (LxD):	61.5x51 mm
Weight:	0.07 kg
EPREL-Nr:	2033767

Scope of delivery:

1 x illuminant