



**The article is no longer in our assortment.**

### Features:

#### EUROLITE TMH XB-230 Moving-Head Beam

High performance beam for 230 W discharge lamp

- Very narrow beam angle with 3°
- With electronic ballast
- Color wheel with 14 different dichroic color filters plus white
- Switchable color change (mode 1: only full colors, mode 2: half colors)
- Rainbow effect with adjustable speed
- 8-facet prism
- Frost-filter
- Gobo wheel with 17 static gobos plus open
- With gobo shake function
- Motorized focus
- Strobe effect with adjustable speed
- Random strobe effect
- Dimmer
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- Switch-mode power supply for operation between 100 and 240 volts
- Control board with graphic LC display and encoder for adjusting the DMX-starting address, PAN/TILT reverse, reset, lamp on/off, operating hours
- DMX-controlled operation or stand-alone operation with master/slave function
- For OSD 7 Reflector 230 W discharge lamp
- Power connection via Neutrik PowerCon socket and included power cable
- DMX-control via every standard DMX-controller
- Gobos
- Beam effect

### Logistic

- The device is cooled by cooling fan
- Control via DMX; stand-alone
- Preprogrammed in LED PC-Control 512
- With a beam angle of 3°

### OMNILUX OSD 7 Reflector 230W Discharge Lamp

OMNILUX OSD technology

- Very short arc
- Compact design
- Reflector lamp
- Long life
- High beam intensity
- Freedom to create smaller and lighter fixtures
- Perfect alignment and placing with lamp replacements in seconds
- Renewed optical system with maximum light output
- High perceived brightness
- Dimmable
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Technical specifications:

|         |          |
|---------|----------|
| Weight: | 19,20 kg |
|---------|----------|

### EUROLITE TMH XB-230 Moving-Head Beam

|                        |   |
|------------------------|---|
| Power supply:          | 100-240 V AC, 50/60 Hz                          |
| Power consumption:     | 300 W   |
| IP classification:     | IP20  |
| Lamp type:             | Discharge lamp                                  |
| Equipment:             | Gobos   |
| Cooling:               | Cooling fan                                     |
| Control:               | DMX; stand-alone                                |
| Preprogrammed in:      | LED PC-Control 512                              |
| Beam angle:            | 3°  |
| Beam angle (1/2 peak): | 3°  |
| Housing color:         | Black   |
| Dimensions:            | Width: 39,5 cm<br>Depth: 32 cm<br>Height: 51 cm |
| Weight:                | 19,14 kg  |
| DMX channels:          | 16  |
| DMX connection:        | 5-pin and 3-pin XLR                             |
| Flash-rate:            | 18 Hz   |
| Color-wheel:           | 14 dichroic filters plus open                   |
| Static gobo-wheel:     | 17 gobos and open                               |
| Maximum PAN-movement:  | 540°  |
| Maximum TILT-movement: | 250°  |
| Beam angle:            | 3°  |

|                         |  |
|-------------------------|--|
| Dimensions (L x W x H): | 395 x 320 x 510 mm                           |
| Legal specifications    |  |
| Special product:        | Not designed for household room illumination |
| Intended use:           | Show effect lighting                         |

#### **OMNILUX OSD 7 Reflector 230W Discharge Lamp**

|                     |                                   |
|---------------------|-----------------------------------|
| Operating voltage:  | 75                                |
| Nominal wattage:    | 230 W                             |
| Base:               | Special                           |
| Lamp type:          | Metal vapour lamp; reflector lamp |
| Lamp specification: | Dimmable                          |
| Color temperature:  | 8000K                             |
| Burning position:   | S180 (universal)                  |
| Lamp life:          | 2000 h                            |
| Luminous flux:      | 10500 lm                          |
| Lamp current:       | 3,3 A                             |
| Dimensions (LxD):   | 61,5x51 mm                        |
| Weight:             | 0,06 kg                           |
| EPREL-Nr:           | 2033771                           |