



### Features:

#### EUROLITE LED TMH-15 Moving Head Zoom Wash

4in1 moving head wash with zoom and 15 W 4in1 RGBW LEDs

- Equipped with seven 15 W quadcolor LEDs with RGBW colors
- Compact lightweight
- Motorized zoom with 11°- 55° beam angle
- Color presets
- Positioning within 630° PAN and 200° TILT
- Stepless RGBW color mixture
- Masterdimmer
- Internal programs
- Strobe effect with 1-18 flashes per second
- Random strobe effect
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-control via built-in microphone
- Control board with graphic LC display for adjusting the DMX-starting address, PAN/TILT reverse, program, reset
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- The device is cooled by cooling fan
- Control via DMX; stand-alone
- Flicker-free

### Logistic

## ROADINGER Flightcase 4x TMH-15 with wheels

Trunk case with castors

- Fitted for 4 devices and accessory
- Additional accessory compartment
- Interior upholstered with foam
- High-quality workmanship with birch multiplex, dark brown laminated
- Aluminum profile frames (25 mm) with rounded edges
- Three-leg, big steel ball corners
- Lid with 2 tip-over locks
- 4 chrome butterfly locks
- 4 chrome case handles
- 4 castors (100 mm), 2 of which with locking brakes
- 4 stacking dishes for stacking the cases
- Castors
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 44.60 kg

---

## EUROLITE LED TMH-15 Moving Head Zoom Wash

Power supply: 100-240 V AC, 50/60 Hz

---

Power consumption: 130 W

---

Lamp type: LED lamp

---

Cooling: Cooling fan

---

Control: DMX; stand-alone

---

Fixtures available for: Light'J; LED PC-Control 512

---

Projection: Flicker-free

---

Beam angle (1/2 peak): 11 - 28°

---

Beam angle (1/10 peak): 25 - 55°

---

Illuminance in Lux (lx):

Narrow red (R)	3m: 702 lx, 6m: 182 lx
Narrow green (G)	3m: 1131 lx, 6m: 298 lx
Narrow blue (B)	3m: 185 lx, 6m: 50 lx
Narrow cold white (CW)	3m: 1139 lx, 6m: 304 lx
Narrow all	3m: 2272 lx, 6m: 600 lx
Wide red (R)	3m: 157 lx, 6m: 42 lx
Wide green (G)	3m: 238 lx, 6m: 65 lx
Wide blue (B)	3m: 54 lx, 6m: 15 lx
Wide cold white (CW)	3m: 329 lx, 6m: 91 lx
Wide all	3m: 562 lx, 6m: 155 lx

---

Housing color: Black

---

Dimensions:

Width:	25 cm
Depth:	15 cm
Height:	33.5 cm

---

Weight: 5.35 kg

---

DMX channels: 13

---

DMX connection: 3-pin XLR

---

Sound-control:	via built-in microphone
Flash-rate:	18 Hz
LED type:	Cree 15 W QCL
LED number:	7
Maximum PAN-movement:	630°
Maximum TILT-movement:	200°
Beam angle:	11° - 28°
Dimensions (L x W x H):	150 x 250 x 335 mm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **ROADINGER Flightcase 4x TMH-15 with wheels**

Maximum load:	100 kg
Transport aid:	Castors
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Dimensions:	Width: 76 cm Depth: 61.5 cm Height: 42 cm
Weight:	23.20 kg
Strength:	7 mm
Outside dimensions (W x D x H):	760 x 615 x 420 mm
Compartment dimensions (W x D x H):	125 x 280 x 300 mm
Accessory compartment (W x D x H):	100 x 610 x 320 mm

#### **Scope of delivery:**

---