

EUROLITE Set 2x LED THA-250F + Case

2x Theater-Spot with fresnel spot including PRO flightcase

Art. No.: 20000161

GTIN:



List price: 2795.31 €

incl. 19% VAT.

Features:

EUROLITE LED THA-250F Theater Spot

Fresnel spotlight (fresnel lens), warm white 200 W LED, CRI >90, quiet, DMX

- 1 powerful LED 200 W COB (chip-on-board) warm white (WW)
- Zoom motor driven; focus manual
- Dimmer electronic; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via RDM; stand-alone; DMX; quick select potentiometer for brightness and Zoom
- Preprogrammed in LED PC-Control 512; Light Captain; Light´J
- Flicker-free
- With a beam angle of 5° - 38°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Trade fair and shop fitting; installation; stage; theater
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x barndoor, 1 x filter frame

Logistic

ROADINGER Flightcase 2x THA-250F with wheels

Trunk case with castors, PRO version

- With accessory compartment
- With 2 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- 4 built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	45,40 kg
---------	----------

EUROLITE LED THA-250F Theater Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	265 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Device fuse:	5 x 20 mm, T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 200 W COB (chip-on-board) warm white (WW)
Flash rate:	1,5 - 12 Hz
Equipment:	Zoom motor driven; focus manual
DMX channels:	3
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; stand-alone; DMX; quick select potentiometer for brightness and Zoom
Preprogrammed in:	LED PC-Control 512; Light Captain; Light'J
Projection:	Flicker-free
PWM frequency:	3600 Hz
Beam angle:	5° - 38°
Beam angle (1/2 peak):	5 - 28°
Beam angle (1/10 peak):	12 - 38°

Color temperature:	2800K
Color rendering index (CRI):	92 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Transport aid:	Rubber feet
Dimensions:	Length: 45,7 cm Width: 33,6 cm Height: 39,9 cm
Weight:	10,00 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x THA-250F with wheels

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Inside dimensions:	91,5 cm x 50 cm x 31 cm
Accessory compartment:	10,5 cm x 50 cm x 35,5 cm
Device compartment:	39 cm x 50 cm x 31 cm
Dimensions:	Width: 97 cm Depth: 54 cm Height: 54 cm
Weight:	21,00 kg