

EUROLITE Set 4x LED THA-40PC bk + Case

4x fanless Pc spot including PRO flightcase with wheels

Art. No.: 20000165

GTIN:



List price: 1902.81 €

incl. 19% VAT.

Features:

EUROLITE LED THA-40PC Theater-Spot bk

Fanless PC spot (DMX), 57 W LED in warm white, color rendering index (CRI) >90

- DMX-controlled operation or stand-alone operation with Master/Slave function
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Functions: dimmer, strobe effects
- Different dimmer curves and dimmer speed (step response) adjustable
- Color temperature 3100 Kelvin
- Manual, stepless zoom 11°-48°
- Metal housing in black or white
- Mounting bracket for installation on a stand or a crossbeam
- Locking possibility at the bracket
- Additional rubber feet when the spot shall be positioned on the floor
- Rotatable barn doors and color filter frame included in the delivery
- Ready for connection via power cord with safety-plug
- Switch-mode power supply for operation between 100 and 240 volts
- LED: 1 x COB (chip-on-board) 57 W warm white (WW)
- Can be operated in 1; 2 CH mode
- The device is cooled by passive convection
- Controlling by Stand-alone; DMX
- Is in EUROLITE LED PC-Control 512 software; Light J Software already preprogrammed
- Flicker-free projection
- With very high color rendering index (CRI)

Logistic

ROADINGER Flightcase 4x THA-40 PC with wheels

PRO flightcase with castors for 4 THA-40 PC

- Fitted for 4 devices and accessory
- Additional accessory compartment
- Interior upholstered with foam
- High-quality workmanship with birch multiplex, dark brown laminated
- Aluminum profile frames (25 mm) with rounded edges
- Three-leg, big steel ball corners
- Lid with 2 tip-over locks
- 4 castors (100 mm), 2 of which with locking brakes
- 2 chrome butterfly locks
- 4 chrome case handles
- 4 stacking dishes for stacking the cases
- Transport aid: With wheels
- Made in Europe

Technical specifications:

Weight: 32,80 kg

EUROLITE LED THA-40PC Theater-Spot bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
IP classification:	IP20
Power connection:	Fixed Power supply cord with safety plug
LED:	1 x COB (chip-on-board) 57 W warm white (WW)
Color temperature:	3100K
DMX channels:	1; 2
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection
Control:	Stand-alone; DMX; EUROLITE LED PC-Control 512 software; Light J Software
Color rendering index (CRI) more than:	90 Ra
Beam angle:	11 - 48°
Beam angle (1/2 peak):	11 - 37°
Beam angle (1/10 peak):	17 - 48°
Illuminance in Lux (lx):	Warm white (WW) 3m: 1656 lx, 6m: 424 lx
Housing color:	Black
Display type:	LCD display
Dimensions:	Length: 27,5 cm Width: 20,5 cm Depth: 25 cm
Weight:	3,85 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
intended use:	show effect lighting

ROADINGER Flightcase 4x THA-40 PC with wheels

Maximum load:	100 kg
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Dimensions:	Width: 78 cm Depth: 52 cm Height: 42,5 cm
Weight:	17,40 kg