

## EUROLITE Set 2x LED THA-60PC + Case

2x PC spots with 60 W COB LED including PRO flightcase

Art. No.: 20000168

GTIN:



**List price: 1069.81 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED THA-60PC Theater-Spot

Spot with 60 W COB LED (RGBW) and plano-convex lens, extremely quiet, DMX

- Equipped with one 60 W COB LED in the colors red, green, blue and white
- With plano-convex lens
- Manual, stepless zoom 7 - 48°
- Small and robust spot with metal housing
- Mounting bracket for installation on a stand or a crossbeam
- Locking possibility at the bracket
- Functions: RGBW color mixture, automatic color change, internal program, dimmer, strobe effects with variable speed, sound-control via built-in microphone sound-control
- Different dimmer curves and dimmer speed (step response) adjustable
- Rotatable barn doors and color filter frame included in the delivery
- Addressing via control panel with LC display
- Ready for connection via power cord with safety-plug
- Switch-mode power supply for operation between 100 and 240 volts
- LED: 1 x COB (chip-on-board) 60 W 4in1 QCL RGBW (homogenous color mix)
- Can be operated in 5; 6; 7 CH mode
- The device is cooled by temperature-controlled fan
- Controlling by Stand-alone; DMX
- Is in Light J Software; EUROLITE LED PC-Control 512 software; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE already preprogrammed
- Flicker-free projection

### Logistic

#### ROADINGER Flightcase 2x THA-40 PC

PRO flightcase for 2 THA-40 PC

- Fitted for two devices and accessories
- Additional accessory compartment
- High-quality workmanship with wood, dark brown laminated
- Aluminum profile frames (25 mm) with rounded edges
- Interior upholstered with foam
- Three-leg, medium-sized steel ball corners
- Lid with 2 tip-over locks
- 2 chrome butterfly locks
- 2 case handles
- Made in Europe

## Technical specifications:

---

Weight: 15,63 kg

---

### EUROLITE LED THA-60PC Theater-Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
IP classification:	IP20
Power connection:	Fixed Power supply cord with safety plug
LED:	1 x COB (chip-on-board) 60 W 4in1 QCL RGBW (homogenous color mix)
DMX channels:	5; 6; 7
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; Light J Software; EUROLITE LED PC-Control 512 software; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Beam angle:	7 - 48°
Beam angle (1/2 peak):	7 - 39°
Beam angle (1/10 peak):	14 - 48°
Housing color:	Black
Dimensions:	Length: 33,4 cm Width: 19,6 cm Depth: 17,3 cm
Weight:	3,74 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Legal specifications	
Special product:	Not designed for household room illumination
intended use:	show effect lighting

### ROADINGER Flightcase 2x THA-40 PC

Maximum load: 50 kg

---

Material:	Birch multiplex, 7 mm
Color:	Black, laminated
Dimensions:	Width: 64,5 cm Depth: 35 cm Height: 29 cm
Weight:	8,15 kg