

## EUROLITE Set 2x LED THA-60PC + Case

2x PC spots with 60 W COB LED including PRO flightcase

Art. No.: 20000168

GTIN: 4026397586282



### Features:

- With plano-convex lens
- Compact design
- 1 LED 60 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
- Dimmer electronic; color change adjustable; color fade adjustable; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX
- Flicker-free
- With mounting bracket
- LCD display
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; restaurants, bars and hotels; theater; advertisement/Shop window
- Very quiet working noise
- Application possibility: Suspended; on stand
- <p>ROADINGER Flightcase 2x THA-40 PC
- <h2 class="featureSatz">Trunk case, PRO version</h2>With accessory compartment
- With 2 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe

### Logistic

EAN / GTIN: 4026397586282

Weight: 15,63 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 16.63 kg

---

### EUROLITE LED THA-60PC Theater Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
DMX channels:	5; 6; 7
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX
Fixtures available for:	Light´J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	7 - 39°
Beam angle (1/10 peak):	14 - 48°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Length: 33.4 cm Width: 19.6 cm Depth: 17.3 cm
Weight:	3.74 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### ROADINGER Flightcase 2x THA-40 PC

Maximum load:	50 kg
Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs

Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	16 cm x 31 cm x 12 cm
Accessory compartment:	10.5 cm x 31 cm x 18 cm
Inside dimensions:	60 cm x 31 cm x 20 cm
Dimensions:	Width: 64.5 cm Depth: 35 cm Height: 29 cm
Weight:	8.15 kg

### **Scope of delivery:**

---

- 1 x spotlight
- 1 x barndoor
- 1 x user manual
- 1 x filter frame