

EUROLITE Set LED KLS Laser Bar FX + M-3 Speaker System Stand

Bar with 2 derbies, 2 spots, white strobe LEDs and laser inklusive speaker stand

Art. No.: 20000172

GTIN: 4026397589108



Features:

- Crossbar with integrated DMX control unit and stand sleeve
 - 2 laser diodes project hundreds of red and green laser beams
 - 2 rotating derbies for mirror ball effects
 - When fog is used, this effect becomes especially attractive
 - Laser; multi beam effect; strobe effect; flower effect
 - 37 integrated show programs
 - The device is cooled by cooling fan
 - Control via stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function
 - Fixtures available for Light´J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
 - With mounting bracket
 - 4 digit 7-segment LED display
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Clubs/dancing school; mobile djs / entertainer; party room; restaurants, bars and hotels; wedding/gala/events
 - Application possibility: On stand
- laser**
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 3 LEDs 3 W SMD 8072 3in1 TCL RGB (homogenous color mix)
2 spots controlled separately
 - With a beam angle of 13°
- light effect**
- 3 LEDs 1 W SMD 8072 R/G/B
2 spots controlled separately

Logistic

EAN / GTIN: 4026397589108
Weight: 12,55 kg
Length: 1.35 m
Width: 0.21 m
Height: 0.58 m
Bulky product

bar

- 4 LEDs 1 W SMD 8072 cold white (CW)
 LEDs controlled separately
- <p>OMNITRONIC M-3 Speaker-System Stand
- <h2 class="featureSatz">Speaker stand, extendible up to 180 cm, maximum load 30 kg</h2>Stable speaker stand for mobile use
- Adjustable height

Technical specifications:

Weight: 12.25 kg

EUROLITE LED KLS Laser Bar FX Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Device fuse:	5 x 20 mm, F 1 A fuse replaceable
Lamp type:	LED lamp
Flash rate:	0 - 30 Hz
DMX channels:	3; 5; 9; 27
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function
Fixtures available for:	Light J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Housing color:	Black
Attachment system:	Tube: 1x Ø 35mm 2x mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 109 cm Depth: 14.5 cm Height: 37 cm
Weight:	9.05 kg
Noise classification:	Class 2 (slight noise)
LED type:	3 x 1 W SMD 8072 R/G/B
LED type:	3 x 3 W SMD 8072 3in1 TCL RGB (homogenous color mix)
Beam angle:	13°

Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	20°
Battery:	1 x 9.0 V E block 6LR61 alkaline manganese included
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm Green (G) 30 mW 532nm
LED type:	4 x 1 W SMD 8072 cold white (CW)
Beam angle (1/2 peak):	7°

OMNITRONIC M-3 Speaker-System Stand

Maximum carrying capacity:	30 kg
Height:	Maximum: 182 cm Minimum: 100 cm
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Steel (powder-coated)
Color:	Black, painted
Weight:	3.20 kg

Scope of delivery:

1 x EUROLITE LED KLS Laser Bar FX Light Set

1 x user manual
 1 x declaration of conformity
 1 x power cord
 1 x foot control
 1 x remote control
 2 x battery
 2 x mounting bracket
 2 x knurled screw
 1 x bag
 2 x washer

1 x OMNITRONIC M-3 Speaker-System Stand

1 x stand
 1 x user manual