

FUTURELIGHT Set 4x PLB-280 + Case

4x PRO spot, beam and washlight Moving Head including PRO flightcase with wheels

Art. No.: 20000175

GTIN:



List price: 9518.81 €

incl. 19% VAT.

Features:

FUTURELIGHT PLB-280 Moving Head Spot/Beam

PRO spot, beam and wash moving-head with 280 W discharge lamp

- Equipped with an Osram Sirius HRI 280 W discharge lamp
- Upgrade via optional wireless receiver module for WDMX operation (Wireless Solution - made in Sweden)
- High PAN/TILT speed
- Spot, beam and due to the use of the frost filter also wash light in one device
- Effect wheel with rotating 6-facet linear prism, 8-facet prism and frost filter
- The prism rotate in both directions and at different speeds
- Strobe effect with adjustable speed
- Random strobe effect
- Motorized focus
- Autofocus
- Motorized zoom with 2 - 10° beam angle (Beam mode) and 5.5 - 23° beam angle (Spot mode)
- Dimmer
- PAN angle switchable between 540° and 630°
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc. (the Li-Ion battery 3.7V, AAA, 10440 is not included)
- Control board with graphic LCD for adjusting the DMX-starting address, PAN/TILT reverse, reset, lamp on/off, operating hours
- DMX-controlled operation or stand-alone operation with master/slave function
- Number of scenes in Program Run can be changed individually

Logistic

- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- Software upload by optional accessory via DMX link
- With Osram Sirius HRI 280 W lamp
- Power connection via Neutrik PowerCon jack and included power cable
- DMX-control via any standard DMX-controller
- Color wheel 13 dichroitic colors and open
Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 14 gobos und open
shake effect
- Gobo wheel with rotating gobos, 9 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for exchanging gobos without tools
- Can be operated in 14; 16; 20; 23 CH mode
- The device is cooled by temperature-controlled fan
- Controlling by Stand-alone; DMX; RDM; W-DMX by wireless solution upgradeable
- Is in EUROLITE LED PC-Control 512 software already preprogrammed
- Effect: Strobe effect; gobo effect; Single Beam

ROADINGER Flightcase 4x PLB-280

PRO flightcase for 4 x PLB-280

- Fitted for 4 devices and accessory
- Additional accessory compartment
- Interior upholstered with foam
- High-quality workmanship with birch multiplex, dark brown laminated
- Aluminum profile frames (25 mm) with rounded edges
- Three-leg, big steel ball corners
- Lid with 2 tip-over locks
- 4 castors (100 mm), 2 of which with locking brakes
- 2 chrome butterfly locks
- 8 chrome case handles
- 4 stacking dishes for stacking the cases
- Transport aid: With wheels
- Made in Europe

Technical specifications:

Weight: 131,80 kg

FUTURELIGHT PLB-280 Moving Head Spot/Beam

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	360 W
IP classification:	IP20
Power connection:	Mains input PowerCON (blue), mounting version Power supply cord with safety plug (provided)
Lamp type:	Discharge lamp
Max. TILT movement:	Exact positioning (16 bit resolution) 270° Auto position correction (feedback)
Max. PAN movement:	Exact positioning (16 bit resolution) 540° Positioning switchable to 630° Auto position correction (feedback)
Flash rate:	0 - 20 Hz

Equipment:	Gobo wheel with rotating gobos; Prism Linear; Prism 8-fold; Focus motor-driven; frost filter; gobo wheel with static gobos; Zoom motor-driven
Color generation:	Color wheel 13 dichroitic colors and open
Gobos:	Gobo wheel with static gobos, 14 gobos und open Outside diameter 16mm Image diameter 12mm Shake effect Gobo wheel with rotating gobos, 9 gobos and open Shake effect Gobos changeable Slot-in gobo system for exchanging gobos without tools
DMX channels:	14; 16; 20; 23
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; RDM; W-DMX by wireless solution upgradeable; EUROLITE LED PC-Control 512 software
Beam angle:	2 - 23°
Beam angle (1/2 peak):	Beam 2 - 10° Spot 5,5 - 23°
Beam angle (1/10 peak):	Spot 5,5 - 23° Beam 2 - 10°
Housing color:	Black
Use of brands:	With OSRAM bulb included
Dimensions:	Width: 40,2 cm Depth: 36,9 cm Height: 53,4 cm
Weight:	19,00 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
energy efficiency class (A++ - E):	G
nominal wattage:	280.00 W
energy consumption:	280.00 kWh/1000h
lamp:	1 x conventional with EEI C included

ROADINGER Flightcase 4x PLB-280

Maximum load:	100 kg
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	40 cm x 34,5 cm x 56 cm
Accessory compartment:	10 cm x 71 cm x 56 cm
Inside dimensions:	93,5 cm x 71 cm x 56 cm

Dimensions:	Width: 98 cm
	Depth: 76 cm
	Height: 83,5 cm
<hr/>	
Weight:	45,00 kg
<hr/>	