

EUROLITE Set 4x LED PMB-8 COB RGB + Case

4x bright bar with 8 x 30 W COB LED, RGB and wide beam angle including PRO flightcase

Art. No.: 20000184

GTIN:



The article is no longer in our assortment.

Features:

EUROLITE LED PMB-8 COB RGB 30W Bar

Bright bar with 8 x 30 W COB LED, good RGB color mixture, wide beam angle

- Equipped with 8 x 30 W COB LEDs in the colors red, green and blue
- Each LED can be controlled individually
- Rugged housing and an appealing design
- Base for standing installation
- Functions: Static colors, RGB color blend, internal programs, dimmer and strobe settings via DMX, Master/Slave
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Comfortable addressing and setting via control panel with LCD and four operating buttons
- Neutrik powerCON terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 8 powerful LEDs 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
- With a beam angle of 60°
- LCD display
- Very quiet working noise

Package contents

- 1 x light effect, 1 x user manual, 1 x power cord

Logistic

ROADINGER Flightcase 4x PMB-8

Trunk case, PRO version

- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Trolley
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

| | |
|---------|----------|
| Weight: | 48,45 kg |
|---------|----------|

EUROLITE LED PMB-8 COB RGB 30W Bar

| | |
|------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 200 W |
| IP classification: | IP20 |
| Power connection: | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x PowerCON (gray), mounting version |
| Lamp type: | LED lamp |
| LED type: | 8 x 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix) |
| Flash rate: | 0 - 18 Hz |
| DMX channels: | 3; 5; 24; 27 |
| DMX input: | 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | Stand-alone; DMX; sound to light via microphone |
| Preprogrammed in: | Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE |
| Beam angle: | 60° |
| Beam angle (1/2 peak): | 60° |
| Housing color: | Black |
| Display type: | LCD display |
| Dimensions: | Length: 88 cm Depth: 15 cm Height: 16,5 cm |

| | |
|-----------------------|--|
| Weight: | 8,20 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x PMB-8

| | |
|--------------------------|--------------------------|
| Aluminum profile frames: | 25 mm |
| Case handle: | 4 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 1 pc/pcs |
| Transport aid: | Trolley |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Black, laminated |
| Device compartment: | 18 cm x 16 cm x 84,5 cm |
| Inside dimensions: | 38 cm x 34 cm x 84,5 cm |
| Dimensions: | Width: 39 cm |
| | Depth: 42,5 cm |
| | Height: 95 cm |
| Weight: | 15,65 kg |