eurolite®

EUROLITE Set 4x LED PMC-25x10W COB RGB + Case







The article is no longer in our assortment.

Features:

EUROLITE LED PMC-25x10W COB RGB 25°

PRO COB performance cluster with 5 x 5 matrix

- Operable in stand-alone mode via control panel with LCD screen or in DMX mode via any commercial DMX controller (occupies max. 79 channels)
- 3, 4, 5, 75, 78 or 79 DMX channels selectable for various applications
- Equipped with 25 x 10 W COB LEDs in the colors red, green and blue
- Each LED can be controlled individually
- Functions: Static colors, RGB color mixture, automatic color change, internal programs, dimmer and strobe settings via DMX, Master/Slave
- Dimmer speed (step response) controllable
- Adjustable white balance
- Various patterns via DMX allow for one-of-a-kind plays of light
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Feed-through output allows to power up to 8 devices
- Switch-mode power supply for operation between 100 and 240 Volts
- Power connection via Neutrik PowerCon jack and included power cable with safety plug
- Control via DMX; RDM; sound to light via microphone
- Preprogrammed in Light J; Light Captain

ROADINGER Flightcase 4x PMC-25

PRO flightcase

- Compartments for 4 PMC-25
- Suitable for EUROLITE LED PMC-25x10W COB RGB 25°

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Interior upholstered with foam
- Three-leg, medium-sized steel ball corners
- 2 hinges
- 1 butterfly lock
- 4 case handle
- Castors
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

| eig | |
|-----|--|
| | |
| | |
| | |

73,00 kg

EUROLITE LED PMC-25x10W COB RGB 25°

| Power supply: | 100-240 V AC, 50/60 Hz | |
|-------------------------|--|--|
| Power consumption: | 290,00 W | |
| IP classification: | IP20 | |
| Lamp type: | LED lamp | |
| Control: | DMX; RDM; sound to light via microphone | |
| Preprogrammed in: | Light´J; Light Captain | |
| Beam angle (1/2 peak): | 25° | |
| Housing color: | Black | |
| Dimensions: | Width: 43,1 cm Depth: 17,9 cm | |
| | Height: 44,8 cm | |
| Weight: | 11,45 kg | |
| DMX channels: | 3/4/5/75/78/79 | |
| DMX connection: | 5-pin and 3-pin XLR | |
| Flash-rate: | 18 Hz | |
| Sound-control: | via built-in microphone | |
| LED number: | 25 | |
| LED type: | Array Cluster 10 W, RGB | |
| Beam angle: | 25° | |
| Dimensions (W x D x H): | 431 x 178,8 x 448 mm | |
| Legal specifications | | |
| Special product: | Not designed for household room illumination | |
| Intended use: | Show effect lighting | |
| | | |

ROADINGER Flightcase 4x PMC-25

| Maximum load: | 100 kg |
|----------------|------------------|
| Transport aid: | Castors |
| Use of brands: | Branded hardware |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| Birch multiplex, 7 mm |
|-----------------------|
| Dark brown, laminated |
| Width: 100 cm |
| Depth: 50 cm |
| Height: 65,5 cm |
| 1000 x 500 x 655 mm |
| 955 x 450 x 425 mm |
| 195 x 450 x 425 mm |
| 26.6 kg |
| |