# eurolite®

# EUROLITE Set 6x LED TMH-6 + Case







# The article is no longer in our assortment.

## Features:

#### EUROLITE LED TMH-6 Moving Head Spot

Bright LED moving head with a 15 W 3in1 LED

- Equipped with a 15 W tricolor LED with RGB colors
- Through the close chip placement of the multichip technology, an exquisite color mix even with short distances to the illuminated surface is provided
- Compact lightweight
- 13 or 5 DMX channels selectable for numerous applications
- Positioning within 540° PAN and 270° TILT
- Stepless RGB color mixture
- Color-macro-function for an easy selection of possible color-combinations
- Gobo-wheel with 9 static gobos plus open
- With gobo-shake function
- Rainbow-effect with adjustable speed
- Programmable color-change speed and strobe effect
- Strobe effect with 1-10 flashes per second
- Exact positioning via 16 bit PAN/TILT movement resolution
- PAN-angle switchable between 540°, 360° and 180° (in sound and auto mode)
- TILT-angle switchable between 270°, 180° and 90° (in sound and auto mode)
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 8 motion macros can be called up via DMX controller
- Sound-controlled via built-in microphone
- Addressing via control panel with 4-digit LED display
- DMX control via every standard DMX controller
- 1 powerful LED
- Gobos
- Gobo effect; beam effect

Logistic

- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain
- With a beam angle of 11° Package contents
- 1 x omega bracket

#### ROADINGER Flightcase 6x TMH-6/7/8/9

Trunk case, PRO version

- Detachable compartments case can also be used as universal transport case
- With 6 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## **Technical specifications:**

Weight:

29,90 kg

#### EUROLITE LED TMH-6 Moving Head Spot

0	•
Power supply:	230 V AC, 50 Hz
Power consumption:	60 W
IP classification:	IP20
Lamp type:	LED lamp
LED type:	1
Max. TILT movement:	270° positioning
Max. PAN movement:	540° positioning
Flash rate:	1 - 10 Hz
Equipment:	Gobos
DMX channels:	5
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	Light J; LED PC-Control 512; Light Captain
Beam angle:	11°
Beam angle (1/2 peak):	11°
Illuminance in Lux (lx):	Red (R) 3m: 27 lx, 6m: 7 lx
	Green (G) 3m: 69 lx, 6m: 18 lx
	Blue (B) 3m: 14 lx, 6m: 4 lx
	All 3m: 112 lx, 6m: 28 lx
Housing color:	Black
Dimensions:	Width: 17 cm
	Depth: 17,5 cm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Height: 24,5 cm
Weight:	3,25 kg
DMX channels:	13/5
DMX connection:	3-pin XLR
Flash-rate:	10 Hz
Sound-control:	via built-in microphone
LED type:	15 W TCL
LED number:	1
Beam angle:	11°
Static gobo-wheel:	9 gobos and open
Maximum PAN-movement:	540°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	170 x 175 x 245 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### ROADINGER Flightcase 6x TMH-6/7/8/9

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	18 cm x 19,5 cm x 24 cm
Inside dimensions:	57,5 cm x 41 cm x 24,5 cm
Dimensions:	Width: 61,5 cm
	Depth: 43 cm
	Height: 33,5 cm
Weight:	10,40 kg