eurolite®

EUROLITE Set 4x LED BAR-252 RGB 10mm 20° black + Case

The article is no longer in our assortment.

Features:

Logistic

EUROLITE LED BAR-252 RGB 10mm 20° black

LED bar with 252 LEDs in red, green and blue, 110 cm length and 20°

- DMX512 control via regular DMX controller
- Sound-control via built-in microphone
- Stand-alone mode functions adjustable via DIP switches
- Color change speed and strobe effect adjustable via DIP switches
- Multi-color color changes
- Master/Slave function
- Ideal for bands, stages or solo entertainers
- Perfect in public places, main halls, lounges
- Illuminants: 252 10 mm LEDs (48 x red, 108 x green and 96 x blue)
- Available in 2 LED beam angles: 20° or 40°
- Advantages of LED technology: long life of the LEDs, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- 252 powerful LEDs 10 mm R/G/B
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in LED PC-Control 512
- With a beam angle of 20°

ROADINGER Flightcase 4x LED BAR-252 RGB

Carrying case, PRO version

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated

- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- Rugged carrying handle
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	18,10 kg

EUROLITE LED BAR-252 RGB 10mm 20° black

Power supply:	230 V AC, 50 Hz
Power consumption:	50,00 W
IP classification:	IP20
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED type:	252 x 10 mm R/G/B
DMX channels:	12
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	LED PC-Control 512
Beam angle:	20°
Beam angle (1/2 peak):	20°
Housing color:	Black
Dimensions:	Length: 107 cm
	Depth: 6,5 cm
	Height: 9 cm
Weight:	2,20 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED BAR-252 RGB

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Carrying handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs

Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Inside dimensions:	106,5 cm x 44 cm x 7,5 cm
Device compartment:	106,5 cm x 6,5 cm x 7,5 cm
Dimensions:	Width: 114,5 cm Depth: 47,5 cm Height: 14,5 cm
Weight:	9,30 kg