eurolite®

EUROLITE Set 4x LED BAR-252 RGBA 10mm 40° black + Case







The article is no longer in our assortment.

Features:

EUROLITE LED BAR-252 RGBA 10mm 40°

Versatile LED-RGBA color changer

- Operable in stand-alone mode or via DMX
- DMX512 control possible via any commercial DMX controller (occupies max.19 channels)
- 4, 6 or 19 DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Comfortable addressing and setting via control panel with LCD display and four operating buttons
- Functions: Static colors, RGBA color blend, internal programs, dimmer and strobe settings via DMX, Master/Slave
- Equipped with 252 x 10 mm LEDs
- Locking possibility at the mounting bracket
- Ready for connection with power cord and safety plug
- Available in 2 LED beam angles: 20° or 40°
- Advantages of high-power LED technology: extreme light output, long life, low power consumption, defacto maintenance free with brilliant light radiation
- Strobe effect
- Control via stand-alone; DMX
- Preprogrammed in Light'J; LED PC-Control 512

ROADINGER Flightcase 4x LED BAR-252 RGB

Carrying case, PRO version

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Logistic

- Aluminum profile frames 30mm with rounded edges
- Rugged carrying handle
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:

19,70 kg

EUROLITE LED BAR-252 RGBA 10mm 40°

| Power supply: | 230 V AC, 50 Hz |
|-------------------------|---|
| Power consumption: | 24 W |
| IP classification: | IP20 |
| Lamp type: | LED lamp |
| DMX channels: | 6; 4 |
| Control: | Stand-alone; DMX |
| Preprogrammed in: | Light'J; LED PC-Control 512 |
| Beam angle (1/2 peak): | 40° |
| Housing color: | Black |
| Dimensions: | Length: 108 cm Depth: 6,5 cm Height: 9 cm |
| Weight: | 2,60 kg |
| DMX channels: | max. 19: 4 / 6 / 19 |
| DMX connection: | 3-pin XLR |
| Sound-control: | via built-in microphone |
| LED type: | 10 mm |
| LED number: | 252 |
| Beam angle: | 40° |
| Dimensions (L x W x H): | 1075 x 65 x 90 mm |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |
| | |

ROADINGER Flightcase 4x LED BAR-252 RGB

| Maximum load: | 25 kg |
|--------------------------|--------------------------|
| Aluminum profile frames: | 30 mm |
| Carrying handle: | 1 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| Use of brands: | Branded hardware |
|---------------------|----------------------------|
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Inside dimensions: | 106,5 cm x 44 cm x 7,5 cm |
| Device compartment: | 106,5 cm x 6,5 cm x 7,5 cm |
| Dimensions: | Width: 114,5 cm |
| | Depth: 47,5 cm |
| | Height: 14,5 cm |
| Weight: | 9,30 kg |
| | |