



The article is no longer in our assortment.

Features:

EUROLITE Audience Blinder 2x100W LED COB 3200K

Audience blinder, wide beam 2 x 100 W COB LED (warm white)

- 3200 K color temperature
- 1, 2 or 4 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: strobe effect with variable speed, dimmer, Master/Slave
- Different dimmer curves and dimmer speed adjustable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks and crossbeam systems
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- 2 powerful LEDs 100 W COB (chip-on-board) warm white (WW)
- Dimmer
- Strobe effect
- Control via DMX
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- With a beam angle of 60°

Logistic

ROADINGER Flightcase 4x Audience Blinder 2xCOB

Trunk case with castors

- Compartments for 4 x Audience Blinder and accessory
- Suitable for 41606100 EUROLITE Audience Blinder 2x50W LED COB 3200K and 41606120 EUROLITE Audience Blinder 2x100W LED COB 3200K
- Interior upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners (chrome)
- 4 castors (100 mm), 2 of which with locking brakes
- 4 stacking dishes for stacking the cases
- 2 hinges
- 2 high-quality butterfly locks
- 4 high-quality plated case handles
- For perfect protection
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Castors
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	41,00 kg
---------	----------

EUROLITE Audience Blinder 2x100W LED COB 3200K

Power supply:	230 V AC, 50 Hz
Power consumption:	260 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED type:	2 x 100 W COB (chip-on-board) warm white (WW)
Flash rate:	1 - 20 Hz
Equipment:	Dimmer
DMX channels:	1; 2; 4
Control:	DMX
Preprogrammed in:	Light'J; LED PC-Control 512; Light Captain
Beam angle:	60°
Beam angle (1/2 peak):	60°
Color temperature:	3200K
Housing color:	Black
Dimensions:	Width: 42 cm Depth: 14 cm Height: 24 cm
Weight:	4,50 kg
DMX channels:	1/2/4
DMX connection:	5-pin and 3-pin XLR

Flash-rate:	20 Hz
LED number:	2
LED type:	Array 100 W, white
Color temperature:	3200 K
Beam angle:	60°
Dimensions (L x W x H):	140 x 420 x 240 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x Audience Blinder 2xCOB

Maximum load:	100 kg
Transport aid:	Castors
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Inside dimensions:	70 cm x 44 cm x 36 cm
Compartment dimensions:	15 cm x 44 cm x 20 cm
Accessory compartment:	10 cm x 44 cm x 36 cm
Dimensions:	Width: 82 cm Depth: 49 cm Height: 59 cm
Weight:	23,00 kg