

EUROLITE Set 5x LED SLS-7 QCL + Case

5x flat spotlight with 7 x 10 W 4in1 LED including practical black soft bag

Art. No.: 20000223

GTIN:







The article is no longer in our assortment.

Features: Logistic

EUROLITE LED SLS-7 QCL 7x10W Floor

Flat spotlight with 7 x 10 W 4in1 LED with RGBW color mixing

- Slim design for space-saving applications
- 7 high-power 10 W RGBW LEDs (4in1)
- Built-in auto and music show programs
- Stepless color blend, color change, color fade, dimmer and strobe effect
- Control panel with LED display for easy configuration
- Flat, lightweight ABS housing with rubber feet
- Sits flat on the floor or inside a truss
- DMX and power terminals intelligently designed for easy wiring
- Swivel mounting bracket
- Mains input and output for power linking up to 8 units
- 7 powerful LEDs 10 W high-power 4in1 QCL RGBW (homogenous color mix)
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- Preprogrammed in LED PC-Control 512; Light Captain
- With a beam angle of 21°

Package contents

- 1 x device, 1 x power cord, 1 x user manual

EUROLITE SB-18 Soft Bag

Practical soft bag for 4 PRO Pixel Slim PAR-12/ SLS-400

- Made of easy-care nylon

- With Outside pocket
- With dividers
- With 5 device compartments
- High-quality workmanship with textile, black
- Interior with foam padding
- 2 carrying straps

Technical specifications:

Weight: 7,93 kg

EUROLITE LED SLS-7 QCL 7x10W Floor

Power consumption: Polassification: IP20	Power supply:	100-240 V AC, 50/60 Hz
Protection class: Protection class II Power connection: Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) Cable length: 1,5 m Power output: 1 x IEC connector (F) mounting version Fuse: 5 x 20 mm, F 1 A fuse replaceable Lamp type: LED lamp LED lamp LED type: 7 x 10 W high-power 4in1 QCL RGBW (homogenous color mix) DMX channels: 5; 6; 8 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function Preprogrammed in: LED PC-Control 512; Light Captain Beam angle: 21° Beam angle (1/10 peak): 41° Housing color: Black Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Risk Group 0 Not designed for household room illumination	Power consumption:	63 W
Power connection: Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) Cable length: 1,5 m Power output: 1 x IEC connector (F) mounting version Fuse: 5 x 20 mm, F 1 A fuse replaceable LED lamp LED type: 7 x 10 W high-power 4in1 QCL RGBW (homogenous color mix) DMX channels: 5; 6; 8 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling: Cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function Preprogrammed in: LED PC-Control 512; Light Captain Beam angle: 21° Beam angle (1/10 peak): 41° Housing color: Black Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	IP classification:	IP20
version power supply cord with safety plug (provided) Cable length: 1,5 m Power output: 1 x IEC connector (F) mounting version Fuse: 5 x 20 mm, F 1 A fuse replaceable Lamp type: LED lamp LED type: 7 x 10 W high-power 4in1 QCL RGBW (homogenous color mix) DMX channels: 5; 6; 8 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function Preprogrammed in: LED PC-Control 512; Light Captain Beam angle: 21° Beam angle (1/12 peak): 21° Beam angle (1/10 peak): 41° Housing color: Black Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Risk Group 0 Not designed for household room illumination	Protection class:	Protection class II
Power output: 1 x IEC connector (F) mounting version Fuse: 5 x 20 mm, F 1 A fuse replaceable LED lamp LED type: 7 x 10 W high-power 4in1 QCL RGBW (homogenous color mix) DMX channels: 5; 6; 8 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling: Cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function Preprogrammed in: LED PC-Control 512; Light Captain Beam angle: 21° Beam angle (1/2 peak): 21° Beam angle (1/2 peak): 41° Housing color: Black Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Power connection:	version power supply cord with safety plug
Fuse: 5 x 20 mm, F 1 A fuse replaceable Lamp type: LED lamp LED type: 7 x 10 W high-power 4in1 QCL RGBW (homogenous color mix) DMX channels: 5; 6; 8 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function Preprogrammed in: LED PC-Control 512; Light Captain Beam angle: 21° Beam angle (1/2 peak): 21° Beam angle (1/10 peak): 41° Housing color: Black Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Cable length:	1,5 m
LED type: LED type: 7 x 10 W high-power 4in1 QCL RGBW (homogenous color mix) DMX channels: 5; 6; 8 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function Preprogrammed in: LED PC-Control 512; Light Captain Beam angle: 21° Beam angle (1/2 peak): 21° Beam angle (1/10 peak): 41° Housing color: Black Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Legal specifications Special product: Not designed for household room illumination	Power output:	1 x IEC connector (F) mounting version
LED type: 7 x 10 W high-power 4in1 QCL RGBW (homogenous color mix) DMX channels: 5; 6; 8 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function Preprogrammed in: LED PC-Control 512; Light Captain Beam angle: 21° Beam angle (1/2 peak): 21° Beam angle (1/10 peak): 41° Housing color: Black Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Fuse:	5 x 20 mm, F 1 A fuse replaceable
(homogenous color mix) DMX channels: 5; 6; 8 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function Preprogrammed in: LED PC-Control 512; Light Captain Beam angle: 21° Beam angle (1/2 peak): 21° Beam angle (1/10 peak): 41° Housing color: Black Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Lamp type:	LED lamp
DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function Preprogrammed in: LED PC-Control 512; Light Captain Beam angle: 21° Beam angle (1/2 peak): 21° Beam angle (1/10 peak): 41° Housing color: Black Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	LED type:	· · · · · · · · · · · · · · · · · · ·
DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: Stand-alone; DMX; sound to light via microphone; master/slave function Preprogrammed in: LED PC-Control 512; Light Captain Beam angle: 21° Beam angle (1/2 peak): 21° Beam angle (1/10 peak): 41° Housing color: Black Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Legal specifications Special product: Not designed for household room illumination	DMX channels:	5; 6; 8
Cooling: Control: Stand-alone; DMX; sound to light via microphone; master/slave function Preprogrammed in: LED PC-Control 512; Light Captain Beam angle: 21° Beam angle (1/2 peak): 21° Beam angle (1/10 peak): 41° Housing color: Black Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Legal specifications Special product: Not designed for household room illumination	DMX input:	1 x 3-pin XLR (M) mounting version
Control: Stand-alone; DMX; sound to light via microphone; master/slave function Preprogrammed in: LED PC-Control 512; Light Captain Beam angle: 21° Beam angle (1/2 peak): 21° Beam angle (1/10 peak): 41° Housing color: Black Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Legal specifications Special product: Not designed for household room illumination	DMX output:	1 x 3-pin XLR (F) mounting version
Preprogrammed in: LED PC-Control 512; Light Captain Beam angle: 21° Beam angle (1/2 peak): 21° Beam angle (1/10 peak): Housing color: Black Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Cooling:	Cooling fan
Beam angle: Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Black Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Control:	
Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Black Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Preprogrammed in:	LED PC-Control 512; Light Captain
Beam angle (1/10 peak): Housing color: Black Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Beam angle:	21°
Housing color: Black Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Beam angle (1/2 peak):	21°
Dimensions: Width: 21 cm Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Beam angle (1/10 peak):	41°
Depth: 11 cm Height: 22 cm Weight: 1,47 kg Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Housing color:	Black
Photobiological safety: Risk Group 0 Legal specifications Special product: Not designed for household room illumination	Dimensions:	Depth: 11 cm
Legal specifications Special product: Not designed for household room illumination	Weight:	1,47 kg
Special product: Not designed for household room illumination	Photobiological safety:	Risk Group 0
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting

EUROLITE SB-18 Soft Bag

Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Textile
Color:	Black
Dimensions:	Width: 47 cm
	Depth: 24 cm
	Height: 30 cm
Weight:	0,60 kg