

## FUTURELIGHT Set 4x Wave LED Moving Bar + Case

4x PRO Moving Head with two tiltable LED bars including PRO flightcase with wheels

Art. No.: 2000236

GTIN: 4026397593570



**List price: 3818.71 €**

incl. 19% VAT.

### Features:

#### FUTURELIGHT Wave LED Moving Bar

PRO moving-head with two tiltable LED bars and six powerful, white beams

- TILT movement for each LED bar separately and steplessly adjustable
- Individual control of each LED
- Perfect as beam effect into the audience
- Narrow beam angle
- Built-in programs
- Shutter sequences
- Electronic dimmer (0-100%)
- Automatic position correction
- Random strobe effect
- Stand-alone, master/slave and DMX mode
- Control panel with LC display for easy configuration
- Built-in scene memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- LED: 6 x high-power 20 W cold white (CW)
- Can be operated in 14; 15; 17; 18 CH mode
- The device is cooled by temperature-controlled fan
- Controlling by RDM; DMX; stand-alone; W-DMX by wireless solution built-in; Sound to light via Microphone
- Preprogrammed in LED PC-Control 512
- Effect: Fan effect

### Logistic

EAN / GTIN: 4026397593570

## ROADINGER Flightcase 4x Wave

PRO flightcase for 4 x FUTURELIGHT Wave LED moving-bar

- Suitable for 4 devices and accessories
- Additional pocket for accessories
- 4 steering rollers Ø100 mm, 2 with brake
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 8 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- With castors
- With 4 built-in stacking trays in the cover
- Made in Europe

## Technical specifications:

---

### FUTURELIGHT Wave LED Moving Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	6 x high-power 20 W cold white (CW)
Max. TILT movement:	Exact positioning (16 bit resolution) 240° Auto position correction (feedback)
Max. PAN movement:	Exact positioning (16 bit resolution) 540° Positioning switchable to 630° Auto position correction (feedback)
Flash rate:	0 - 20 Hz
DMX channels:	14; 15; 17; 18
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX; stand-alone; W-DMX by wireless solution built-in; Sound to light via Microphone; LED PC-Control 512
Beam angle:	2,5°
Beam angle (1/2 peak):	2,5°
Housing color:	Black
Dimensions:	Width: 46,8 cm Depth: 25 cm Height: 32,5 cm
Weight:	10,60 kg

### Legal specifications

---

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **ROADINGER Flightcase 4x Wave**

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handles:	8 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	Castors 4 x built-in stacking trays in the cover
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Middle compartment:	10 cm x 50 cm x 32,5 cm
Device compartment:	49 cm x 25 cm x 32 cm
Inside dimensions:	1,08 m x 50 cm x 32,5 cm
Dimensions:	Width: 1,15 m Depth: 61,5 cm Height: 57 cm
Weight:	26,70 kg