

FUTURELIGHT Set 4x Wave LED Moving Bar + Case

4x PRO moving head with two tiltable LED bars including PRO flightcase with wheels

Art. No.: 20000236

GTIN: 4026397593570



The article is no longer in our assortment.

Features:

FUTURELIGHT Wave LED Moving Bar

PRO moving head with two tiltable LED bars and six powerful, white beams

- TILT movement for each LED bar separately and steplessly adjustable
- Individual control of each LED
- Perfect as beam effect into the audience
- Narrow beam angle
- Built-in programs
- Shutter sequences
- Electronic dimmer (0-100%)
- Automatic position correction
- Random strobe effect
- Stand-alone, master/slave and DMX mode
- Control panel with LC display for easy configuration
- Built-in scene memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- 6 powerful LEDs 20 W high-power cold white (CW)
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Fan effect
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; stand-alone; sound to light via microphone
- Preprogrammed in LED PC-Control 512
- With a beam angle of 2,5°

Logistic

EAN / GTIN: 4026397593570

ROADINGER Flightcase 4x Wave

PRO flightcase for 4 x FUTURELIGHT Wave LED moving-bar

- With 4 device compartments
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 8 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

FUTURELIGHT Wave LED Moving Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED type:	6 x 20 W high-power cold white (CW)
Max. TILT movement:	240° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540°, 630° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 20 Hz
DMX channels:	14; 15; 17; 18
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX; stand-alone; sound to light via microphone
Preprogrammed in:	LED PC-Control 512
Beam angle:	2,5°
Beam angle (1/2 peak):	2,5°
Housing color:	Black
Dimensions:	Width: 46,8 cm Depth: 25 cm Height: 32,5 cm
Weight:	10,60 kg

Legal specifications

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x Wave

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	8 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Middle compartment:	10 cm x 50 cm x 32,5 cm
Device compartment:	49 cm x 25 cm x 32 cm
Inside dimensions:	108 cm x 50 cm x 32,5 cm
Dimensions:	Width: 115 cm Depth: 61,5 cm Height: 57 cm
Weight:	26,70 kg