

FUTURELIGHT Set 4x Color Wave LED Moving Bar + Case

4x moving head with two tiltable LED bars and colorful beams including PRO flightcase

Art. No.: 20000238

GTIN: 4026397593594



Features:

- TILT movement for each LED bar separately and steplessly adjustable
- Individual control of each LED
- Built-in programs
- Color presets
- Shutter sequences
- Electronic dimmer (0-100%)
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- PAN angle switchable between 540° and 630°
- Random strobe effect
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- 6 LEDs 10 W high-power 4in1 RGBW
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Fan effect
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; stand-alone; sound to light via microphone
- With a beam angle of 2.5°
- <p>ROADINGER Flightcase 4x Wave
- <h2 class="featureSatz">Trunk case with castors</h2>With 4 device compartments
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated

Logistic

EAN / GTIN: 4026397593594

- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 8 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 67.90 kg

FUTURELIGHT Color Wave LED Moving Bar

| | |
|--------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 120 W |
| Power connection: | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x PowerCON (gray), mounting version |
| Lamp type: | LED lamp |
| LED type: | 6 x 10 W high-power 4in1 RGBW |
| Max. TILT movement: | 240° exact positioning (16 bit resolution) auto position correction (feedback) |
| Max. PAN movement: | 540°, 630° exact positioning (16 bit resolution) auto position correction (feedback) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 18; 17 |
| DMX input: | 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | RDM; DMX; stand-alone; sound to light via microphone |
| Fixtures available for: | LED PC-Control 512 |
| Beam angle (1/2 peak): | 2.5° |
| Illuminance in Lux (lx): | Red (R) 3m: 1713 lx, 6m: 655 lx Green (G) 3m: 2074 lx, 6m: 868 lx Blue (B) 3m: 861 lx, 6m: 217 lx Cold white (CW) 3m: 4037 lx, 6m: 452 lx |
| Housing color: | Black |
| Dimensions: | Width: 46.8 cm Depth: 25 cm Height: 32.5 cm |
| Weight: | 10.30 kg |

| | |
|------------------|--|
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x Wave

| | |
|--------------------------|---|
| Maximum load: | 100 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 8 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | 4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Middle compartment: | 10 cm x 50 cm x 32.5 cm |
| Device compartment: | 49 cm x 25 cm x 32 cm |
| Inside dimensions: | 108 cm x 50 cm x 32.5 cm |
| Dimensions: | Width: 115 cm Depth: 61.5 cm Height: 57 cm |
| Weight: | 26.70 kg |

Scope of delivery: