

OMNITRONIC Set WMT-1M UHF transmitter + UHF-502 headset

Art. No.: 20000243 GTIN:







The article is no longer in our assortment.

Features:

OMNITRONIC WMT-1M UHF Transmitter, mono

Wireless mono audio transmission system, 823-832 MHz

- Wireless audio transmission system with UHF PLL technology
- For wireless transmission of audio line and microphone signals with one transmitter and one or more receivers
- Duplex gap 823-832 MHz
- Parallel use of up to 4 transmitters possible
- Compatible with MOM-10BT4 system
- 16 channels selectable
- Audio line input (3.5 mm jack) and microphone input (mini XLR)
- Volume level control
- Operation via 2 batteries or rechargeable batteries size AA
- Built-in charging function via micro USB port with LED indicator
- Supports operation and simultaneous charging
- Robust metal fixing clip
- Incl. USB charging cable and 3.5 mm audio cable
- License-free and approved in large parts of the EU
- Operating range up to 50m
- UHF 823 832 MHz License-free and approved in large parts of Europe

Package contents

- 1 x receiver, 1 x jack cable, 1 x USB cable, 2 x battery, 1 x user manual, 1 x declaration of conformity

OMNITRONIC UHF-502 Headset for Bodypack

Headset for UHF-502 bodypack transmitter

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Lightweight design for optimum wearer comfort
- Gooseneck
- One-sided cable run
- Connection cable with 3-pin mini XLR plug
- Foam windscreen
- Color: black
- Polar pattern: Cardioid

Technical specifications:

Weight:

0,23 kg

OMNITRONIC WMT-1M UHF Transmitter, mono

Power supply:	5V DC 3V DC
Power connection:	Mains input via micro USB (F) mounting version included
	Battery/battery pack
Battery:	2 x Mignon (AA) included
S/N ratio:	>90 dB
Range:	Range up to 50m
Frequency band:	UHF 823 - 832 MHz
Frequency stability:	± 0,01 %
RF power output:	10 mW
Modulation:	FM
Frequency selection:	16 switchable frequencies
Pilot frequency:	32,768 kHz
Control elements:	Power switch, level control, frequency selector switch
Status LED:	Power
Connections:	Input: microphone via 1 x mini XLR (M) 3-pin mounting version 1 V
	Input: AUX via 1 x 3.5 mm jack (stereo) 3,5 V
Switch:	On/off switch
Material:	Plastic
Color:	Black
Dimensions:	Width: 6,7 cm
	Depth: 3,0 cm
	Height: 11,2 cm
Weight:	0,20 kg

OMNITRONIC UHF-502 Headset for Bodypack

Туре:	Headset microphone
Capsule type:	Condenser
Polar pattern:	Cardioid

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Frequency range:	50 - 15000 Hz
Frequency selection:	Switchable frequencies
Weight:	0,03 kg
Туре:	Electret
Directivity pattern:	Cardioid
Sensitivity:	-49 dB
Impedance:	680 ohms
S/N ratio:	>63 dB
Power supply:	2-10 V DC
Connection:	cable with 3-pin mini XLR plug
Cable length:	approx. 1 m
Capsule:	D = 9.7 mm