



Features:**OMNITRONIC WMT-1M UHF Transmitter, mono**

Wireless mono audio transmission system, 823-832 MHz

- Wireless audio transmission system with UHF PLL technology
- For wireless transmission of audio line and microphone signals with one transmitter and one or more receivers
- Duplex gap 823-832 MHz
- Parallel use of up to 4 transmitters possible
- Compatible with MOM-10BT4 system
- 16 channels selectable
- Audio line input (3.5 mm jack) and microphone input (mini XLR)
- Volume level control
- Operation via 2 batteries or rechargeable batteries size AA
- Built-in charging function via micro USB port with LED indicator
- Supports operation and simultaneous charging
- Robust metal fixing clip
- Incl. USB charging cable and 3.5 mm audio cable
- License-free and approved in large parts of the EU
- Operating range up to 50m
- UHF 823 - 832 MHz License-free and approved in large parts of Europe

Logistic**OMNITRONIC UHF-502 Headset for Bodypack**

Headset for UHF-502 bodypack transmitter

- Lightweight design for optimum wearer comfort
- Gooseneck

- One-sided cable run
- Connection cable with 3-pin mini XLR plug
- Foam windscreen
- Color: black
- Polar pattern: Cardioid

Technical specifications:

Weight: 0.23 kg

OMNITRONIC WMT-1M UHF Transmitter, mono

Power supply:	5V DC 3V DC
Power connection:	Mains input via micro USB (F) mounting version included Battery/battery pack
Battery:	2 x Mignon (AA) included
S/N ratio:	>90 dB
Range:	Range up to 50m
Frequency band:	UHF 823 - 832 MHz
Frequency stability:	± 0.01 %
RF power output:	10 mW
Modulation:	FM
Frequency selection:	16 switchable frequencies
Pilot frequency:	32.768 kHz
Control elements:	Power switch, level control, frequency selector switch
Status LED:	Power
Connections:	Input: microphone via 1 x mini XLR (M) 3-pin mounting version 1 V Input: AUX via 1 x 3.5 mm jack (stereo) 3.5 V
Switch:	On/off switch
Material:	Plastic
Color:	Black
Dimensions:	Width: 6.7 cm Depth: 3.0 cm Height: 11.2 cm
Weight:	0.20 kg

OMNITRONIC UHF-502 Headset for Bodypack

Type:	Headset microphone
Capsule type:	Condenser
Polar pattern:	Cardioid
Frequency range:	50 - 15000 Hz

Frequency selection:	Switchable frequencies
Weight:	0.03 kg
Type:	Electret
Directivity pattern:	Cardioid
Sensitivity:	-49 dB
Impedance:	680 ohms
S/N ratio:	>63 dB
Power supply:	2-10 V DC
Connection:	cable with 3-pin mini XLR plug
Cable length:	approx. 1 m
Capsule:	D = 9.7 mm

Scope of delivery:

- 1 x receiver
- 1 x jack cable
- 1 x USB cable
- 2 x battery
- 1 x user manual
- 1 x declaration of conformity