



The article is no longer in our assortment.

Features:

EUROLITE LED TSL-750 Scan

Scanner with 75 W LED, gobos, rotating prism, color wheel, motorized focus

- Equipped with a 75 W LED
- 13 or 15 DMX channel mode selectable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-controlled via built-in microphone
- Internal programs
- Color wheel with 8 dichroic color filters and white
- Rainbow effect with adjustable speed
- Gobo-wheel with 7 rotating gobos plus open
- Gobo shake function
- Rotating 3-facet prism
- Exact positioning via 16 bit PAN/TILT movement resolution
- Strobe effect with adjustable speed
- Motorized focus
- Electronic dimmer
- Lightbeam with 14° radiation angle
- Control board with graphic LC display and four operating buttons for adjusting the DMX starting address, PAN/TILT reverse
- Switch-mode power supply for operation between 100 and 240 Volts
- DMX control via every standard DMX controller
- 1 powerful LED 75 W COB (chip-on-board) cold white (CW)
- Exact positioning (16 bit resolution)
- Gobos
- Gobo effect
- Color wheel with 8 dichroic filters plus open

Logistic

- Gobo wheel with rotating gobos, 7 gobos and open
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 14°

ROADINGER Flightcase 2x TSL-750/TSL-1200

Trunk case

- With 2 device compartments
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- Rugged carrying handle
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Made in Germany
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	27,40 kg
---------	----------

EUROLITE LED TSL-750 Scan

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	1 x 75 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	80° exact positioning (16 bit resolution)
Max. PAN movement:	175° exact positioning (16 bit resolution)
Flash rate:	0 - 18 Hz
Equipment:	Gobos
Color generation:	Color wheel with 8 dichroic filters plus open
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open
DMX channels:	13; 15
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone
Preprogrammed in:	Light´J; LED PC-Control 512; Light Captain
Projection:	Flicker-free

Beam angle:	14°
Beam angle (1/2 peak):	14°
Housing color:	Black
Dimensions:	Width: 26 cm Depth: 47,5 cm Height: 22,5 cm
Weight:	6,95 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x TSL-750/TSL-1200

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Carrying handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	23 cm x 27 cm x 46 cm
Middle compartment:	10,5 cm x 29 cm x 46 cm
Inside dimensions:	64 cm x 29 cm x 46 cm
Dimensions:	Width: 68,5 cm Depth: 33,5 cm Height: 57 cm
Weight:	13,50 kg