

EUROLITE Set LED A60 230V 5W E27 multicolor RC + Triangle base black Art. No.: 20000276

Decorative illumination with LED technology includingl base

GTIN









The article is no longer in our assortment.

Features: Logistic

OMNILUX LED A60 230V 5W E27 multicolor RC

Decorative illumination with remote control

- Color change LED lamp with remote control (included in delivery)
- Easy to change
- 11 colors and white
- Expanded beam angle
- With memory function
- High quality standard
- Dimmable
- Hot restrike
- Control via IR remote control

Package contents

- 1 x remote control

EUROLITE Triangle Base black

Design base with E-27 socket

- Distinctive base for 60 W lamp
- Can also be used with UV lamp
- Control via on/off switch at cable
- For application areas such as: Party room; decoration

Package contents

- 1 x device, 1 x user manual

Technical specifications:

Weight: 0,34 kg

OMNILUX LED A60 230V 5W E27 multicolor RC

built-in	IP classification:	IP20
Base: Lamp type: LED lamp; high voltage lamp Lamp specification: Dimmable Hot restrike Beam angle: 120° Color generation: Multicolor Control: IR remote control Color of light: Fading colors Lead time: 1 s Construction: Bulb Operating temperature max.: 40° C Operating temperature min.: 20° C Burning position: S180 (universal) Dimensions (LxD): 1 x button cell 3.0 V CR2025 lithium manganese built-in	Voltage (lamps):	230 V, AC
Lamp type: Lamp specification: Dimmable Hot restrike Beam angle: 120° Color generation: Multicolor Control: IR remote control Color of light: Fading colors Lead time: 1 s Construction: Bulb Operating temperature max.: 40° C Operating temperature min.: 20° C Burning position: S180 (universal) Dimensions (LxD): 1 x button cell 3.0 V CR2025 lithium manganese built-in	Nominal wattage:	5 W
Lamp specification: Dimmable Hot restrike Beam angle: Color generation: Multicolor Control: IR remote control Color of light: Fading colors Lead time: 1 s Construction: Bulb Operating temperature max.: 40° C Operating temperature min.: 20° C Burning position: S180 (universal) Dimensions (LxD): 112x60 mm Weight: 0,05 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in	Base:	E27
Hot restrike Beam angle: 120° Color generation: Multicolor Control: IR remote control Color of light: Fading colors Lead time: 1 s Construction: Bulb Operating temperature max.: 40° C Operating temperature min.: 20° C Burning position: S180 (universal) Dimensions (LxD): 112x60 mm Weight: 0,05 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in	Lamp type:	LED lamp; high voltage lamp
Color generation: Multicolor IR remote control Color of light: Fading colors Lead time: 1 s Construction: Bulb Operating temperature max.: 40° C Operating temperature min.: 20° C Burning position: S180 (universal) Dimensions (LxD): 112x60 mm Weight: 0,05 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in	Lamp specification:	
Control: IR remote control Color of light: Fading colors Lead time: 1 s Construction: Bulb Operating temperature max.: 40° C Operating temperature min.: 20° C Burning position: S180 (universal) Dimensions (LxD): 112x60 mm Weight: 0,05 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in	Beam angle:	120°
Color of light: Fading colors Lead time: 1 s Construction: Bulb Operating temperature max.: 40° C Operating temperature min.: 20° C Burning position: S180 (universal) Dimensions (LxD): 112x60 mm Weight: 0,05 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in	Color generation:	Multicolor
Lead time: Construction: Bulb Operating temperature max.: 40° C Operating temperature min.: 20° C Burning position: S180 (universal) Dimensions (LxD): 112x60 mm Weight: 0,05 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in	Control:	IR remote control
Construction: Bulb Operating temperature max.: 40° C Operating temperature min.: 20° C Burning position: S180 (universal) Dimensions (LxD): 112x60 mm Weight: 0,05 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in	Color of light:	Fading colors
Operating temperature max.: 40° C Operating temperature min.: 20° C Burning position: S180 (universal) Dimensions (LxD): 112x60 mm Weight: 0,05 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in	Lead time:	1 s
Operating temperature min.: 20° C Burning position: S180 (universal) Dimensions (LxD): 112x60 mm Weight: 0,05 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in	Construction:	Bulb
Burning position: Dimensions (LxD): 112x60 mm Weight: 0,05 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in	Operating temperature max.:	40° C
Dimensions (LxD): 112x60 mm Weight: 0,05 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in	Operating temperature min.:	20° C
Weight: 0,05 kg Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in	Burning position:	S180 (universal)
Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in	Dimensions (LxD):	112x60 mm
Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in	Weight:	0,05 kg
built-in	Remote control	
Legal specifications	Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
3	Legal specifications	
Special product: Not designed for household room illumination	Special product:	Not designed for household room illumination
Intended use: Show effect lighting	Intended use:	Show effect lighting

EUROLITE Triangle Base black

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 60 W
Power connection:	Fixed power supply cord with Euro plug
Cable construction:	2 x 0,75 mm² H03VVH2-F
Cable length:	Approx. 1,8 m
Base:	E27
Control:	On/off switch at cable
Color:	Black
Dimensions:	Width: 15 cm

Depth: 15 cm Height: 10 cm

Weight: 0,29 kg