

# EUROLITE Set 4x AKKU UP-4 QCL Spot QuickDMX + Case

4 uplights with battery, without cable, in flightcase

Art. No.: 20000277

GTIN:







List price: 1605.31 €

incl. 19% VAT.

Features: Logistic

#### **EUROLITE AKKU UP-4 QCL Spot QuickDMX**

Bright Uplight with 4 x 8 W 4in1 LED and QuickDMX transceiver

- Integrated QuickDMX transceiver for wireless DMX control
- Battery operation up to 9,5h depending on program used
- 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone
- Flicker-free
- With a beam angle of 22°
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Dimmer speed (step response) adjustable; Dimmer electronic; color blend stepless; color change adjustable
- Strobe effect
- Preprogrammed in Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- Mains input and output for power linking up to 8 units
- Integrated automatic charging of the battery and status indicator
- With bracket for floor use
- Cordless, flexible and versatile
- Silent operation
- Application possibility: Standing

#### Package contents

 1 x spotlight, 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x remote control, 1 x battery

### ROADINGER Flightcase 4x AKKU UP 4 QCL Spot QuickDMX

Carrying case, PRO version

- Cable bushing allows loading the devices inside
- With accessory compartment
- With 4 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## **Technical specifications:**

#### **EUROLITE AKKU UP-4 QCL Spot QuickDMX**

Power consumption:  IP classification:  IP20  Protection class:  Protection class I  Power connection:  Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)  Cable length:  Approx. 1 m  Power output:  1 x P-Con (gray), mounting version  Battery pack type:  1 x lithium ion 14,8 V, 7800 mAh, 115,44 Wh  Battery pack:  Battery operation up to 9,5h depending on program used Recharging time 3h  Lamp type:  LED lamp  LED type:  4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)  DMX channels:  3; 4; 6; 8; 10  DMX input:  1 x 3-pin XLR (M) mounting version IP  DMX output:  1 x 3-pin XLR (F) mounting version IP  Cooling:  Passive convection cooling  Control:  DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone  Preprogrammed in:  Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 2x4; LED EASY OPERATOR DELUXE; Light Captain  Projection:  Flicker-free  Carrier frequency:  2,4 GHz	Power supply:	100-240 V AC, 50/60 Hz
Protection class:  Protection class I  Power connection:  Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)  Cable length:  Approx. 1 m  Power output:  1 x P-Con (gray), mounting version  Battery pack type:  1 x lithium ion 14,8 V, 7800 mAh, 115,44 Wh  Battery pack:  Battery operation up to 9,5h depending on program used Recharging time 3h  Lamp type:  LED lamp  LED type:  4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)  DMX channels:  3; 4; 6; 8; 10  DMX input:  1 x 3-pin XLR (M) mounting version IP  DMX output:  1 x 3-pin XLR (F) mounting version IP  Cooling:  Passive convection cooling  Control:  DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone  Preprogrammed in:  Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain	Power consumption:	50 W
Power connection:  Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)  Approx. 1 m  Power output:  1 x P-Con (gray), mounting version  Battery pack type:  1 x lithium ion 14,8 V, 7800 mAh, 115,44 Wh  Battery pack:  Battery operation up to 9,5h depending on program used Recharging time 3h  Lamp type:  LED lamp  LED type:  4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)  DMX channels:  3; 4; 6; 8; 10  DMX input:  1 x 3-pin XLR (M) mounting version IP  DMX output:  1 x 3-pin XLR (F) mounting version IP  Cooling:  Passive convection cooling  Control:  DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone  Preprogrammed in:  Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain	IP classification:	IP20
Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)  Cable length: Approx. 1 m  Power output: 1 x P-Con (gray), mounting version  Battery pack type: 1 x lithium ion 14,8 V, 7800 mAh, 115,44 Wh  Battery pack: Battery operation up to 9,5h depending on program used Recharging time 3h  Lamp type: LED lamp  LED lamp  LED type: 4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)  DMX channels: 3; 4; 6; 8; 10  DMX input: 1 x 3-pin XLR (M) mounting version IP  DMX output: 1 x 3-pin XLR (F) mounting version IP  Cooling: Passive convection cooling  Control: DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone  Preprogrammed in: Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain	Protection class:	Protection class I
Power output:  1 x P-Con (gray), mounting version  Battery pack type:  1 x lithium ion 14,8 V, 7800 mAh, 115,44 Wh  Battery pack:  Battery operation up to 9,5h depending on program used Recharging time 3h  Lamp type:  LED lamp  LED type:  4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)  DMX channels:  3; 4; 6; 8; 10  DMX input:  1 x 3-pin XLR (M) mounting version IP  DMX output:  1 x 3-pin XLR (F) mounting version IP  Cooling:  Passive convection cooling  Control:  DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone  Preprogrammed in:  Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR DELUXE; Light Captain  Projection:  Flicker-free	Power connection:	Mains input via P-Con (blue), mounting version
Battery pack type:  1 x lithium ion 14,8 V, 7800 mAh, 115,44 Wh  Battery pack:  Battery operation up to 9,5h depending on program used Recharging time 3h  Lamp type:  LED lamp  LED type:  4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)  DMX channels:  3; 4; 6; 8; 10  DMX input:  1 x 3-pin XLR (M) mounting version IP  DMX output:  1 x 3-pin XLR (F) mounting version IP  Cooling:  Passive convection cooling  Control:  DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone  Preprogrammed in:  Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR DELUXE; Light Captain  Projection:  Flicker-free	Cable length:	Approx. 1 m
Battery pack:  Battery operation up to 9,5h depending on program used Recharging time 3h  Lamp type:  LED lamp  LED type:  4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)  DMX channels:  3; 4; 6; 8; 10  DMX input:  1 x 3-pin XLR (M) mounting version IP  DMX output:  1 x 3-pin XLR (F) mounting version IP  Cooling:  Passive convection cooling  Control:  DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone  Preprogrammed in:  Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR DELUXE; Light Captain  Projection:  Flicker-free	Power output:	1 x P-Con (gray), mounting version
program used Recharging time 3h  Lamp type:  LED lamp  LED type:  4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)  DMX channels:  3; 4; 6; 8; 10  DMX input:  1 x 3-pin XLR (M) mounting version IP  DMX output:  1 x 3-pin XLR (F) mounting version IP  Cooling:  Passive convection cooling  Control:  DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone  Preprogrammed in:  Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR DELUXE; Light Captain  Projection:  Flicker-free	Battery pack type:	1 x lithium ion 14,8 V, 7800 mAh, 115,44 Wh
Lamp type:  LED lamp  LED type:  4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)  DMX channels:  3; 4; 6; 8; 10  DMX input:  1 x 3-pin XLR (M) mounting version IP  DMX output:  1 x 3-pin XLR (F) mounting version IP  Cooling:  Passive convection cooling  Control:  DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone  Preprogrammed in:  Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR DELUXE; Light Captain  Projection:  Flicker-free	Battery pack:	program used
LED type:  4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)  DMX channels:  3; 4; 6; 8; 10  DMX input:  1 x 3-pin XLR (M) mounting version IP  DMX output:  1 x 3-pin XLR (F) mounting version IP  Cooling:  Passive convection cooling  Control:  DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone  Preprogrammed in:  Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR DELUXE; Light Captain  Projection:  Flicker-free		Recharging time 3h
(homogenous color mix)  DMX channels: 3; 4; 6; 8; 10  DMX input: 1 x 3-pin XLR (M) mounting version IP  DMX output: 1 x 3-pin XLR (F) mounting version IP  Cooling: Passive convection cooling  Control: DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone  Preprogrammed in: Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR DELUXE; Light Captain  Projection: Flicker-free	Lamp type:	LED lamp
DMX input:  1 x 3-pin XLR (M) mounting version IP  DMX output:  1 x 3-pin XLR (F) mounting version IP  Cooling:  Passive convection cooling  Control:  DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone  Preprogrammed in:  Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR DELUXE; Light Captain  Projection:  Flicker-free	LED type:	
DMX output:  1 x 3-pin XLR (F) mounting version IP  Cooling:  Passive convection cooling  DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone  Preprogrammed in:  Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain  Projection:  Flicker-free	DMX channels:	3; 4; 6; 8; 10
Cooling:  Passive convection cooling  DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone  Preprogrammed in:  Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR DELUXE; Light Captain  Projection:  Flicker-free	DMX input:	1 x 3-pin XLR (M) mounting version IP
Control:  DMX; stand-alone; QuickDMX; IR remote control; Sound to light via Microphone  Preprogrammed in:  Light'J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain  Projection:  Flicker-free	DMX output:	1 x 3-pin XLR (F) mounting version IP
Preprogrammed in:  Light ´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain  Projection:  Flicker-free	Cooling:	Passive convection cooling
4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain  Projection: Flicker-free	Control:	
	Preprogrammed in:	4x4; LED EASY OPERATOR 4x6; LED EASY
Carrier frequency: 2,4 GHz	Projection:	Flicker-free
	Carrier frequency:	2,4 GHz

Beam angle:	22°
Beam angle (1/2 peak):	22°
Beam angle (1/10 peak):	32°
Housing color:	Black
Attachment system:	Bracket for floor use
Dimensions:	Width: 16,7 cm
	Depth: 13,8 cm
	Height: 18,8 cm
Weight:	3,59 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## ROADINGER Flightcase 4x AKKU UP 4 QCL Spot QuickDMX

Maximum load:	25 kg
Aluminum profile frames:	25 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	14,5 cm x 15,5 cm x 12 cm
Inside dimensions:	44 cm x 35 cm x 19,5 cm
Accessory compartment:	10 cm x 35 cm x 17 cm
Dimensions:	Width: 48,5 cm
	Depth: 39,5 cm
	Height: 26 cm
Weight:	6,20 kg