

## EUROLITE Set 4x AKKU UP-4 QCL Spot QuickDMX + Case

4 uplights with battery, without cable, in flightcase

Art. No.: 2000277

GTIN:



### Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 9.5h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
- Dimmer speed (step response) adjustable; Dimmer electronic; color blend stepless; color change adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; IR remote control; sound to light via microphone
- Flicker-free
- With a beam angle of 22°
- With bracket for floor use
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: Standing
- <p>ROADINGER Flightcase 4x AKKU UP 4 QCL Spot QuickDMX
- <h2 class="featureSatz">Carrying case, PRO version</h2>Cable bushing allows loading the devices inside
- With accessory compartment
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges

### Logistic

- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 20.56 kg

---

### EUROLITE AKKU UP-4 QCL Spot QuickDMX

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1 m
Power output:	1 x P-Con (gray), mounting version
Battery pack type:	1 x lithium ion 14.8 V, 7800 mAh, 115.44 Wh
Battery pack:	Battery operation up to 9.5h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	4 x 8 W SMD 9080 4in1 RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; QuickDMX; IR remote control; sound to light via microphone
Fixtures available for:	Light J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle (1/2 peak):	22°
Beam angle (1/10 peak):	32°
Housing color:	Black
Attachment system:	Bracket for floor use
Dimensions:	Width: 16.7 cm Depth: 13.8 cm Height: 18.8 cm
Weight:	3.59 kg

Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **ROADINGER Flightcase 4x AKKU UP 4 QCL Spot QuickDMX**

Maximum load:	25 kg
Aluminum profile frames:	25 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	14.5 cm x 15.5 cm x 12 cm
Inside dimensions:	44 cm x 35 cm x 19.5 cm
Accessory compartment:	10 cm x 35 cm x 17 cm
Dimensions:	Width: 48.5 cm Depth: 39.5 cm Height: 26 cm
Weight:	6.20 kg

#### **Scope of delivery:**

- 1 x spotlight
- 1 x user manual
- 1 x declaration of conformity
- 1 x power cord
- 1 x remote control
- 1 x battery