

EUROLITE Set PAR-30 Spot bk + PAR-30 230V SMD 11W E-27 LED 6500K Art. No.: 20000286
PAR-30 housing with E-27 socket including PAR-30 lamp with LED technology

GTIN:



List price: 31.54 €

incl. 19% VAT.

Features:

EUROLITE PAR-30 Spot black

PAR-30 housing with E-27 socket (with plug + cable)

- Delivery completely wired with E27 socket and color filter-frame
- Easy installation with silicone cable and power-plug
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter-frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- With adjustable mounting-bracket to be connected with mounting-hook
- Blackened tube for precise light-output
- For decoration or display windows, discotheques
- Suitable for different spot angles
- Small lighting-systems can also be realized with a small budget
- Via color filter frame
- Controlling by plug and play
- For PAR 30

Logistic

OMNILUX PAR-30 230V SMD 11W E-27 LED 6500K

PAR-30 LED lamp

- For E-27 socket
- Easy replacement of lamps
- Power saving
- Environmentally friendly
- Easy installation

Technical specifications:

Weight: 720 g

EUROLITE PAR-30 Spot black

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 100 W
IP classification:	IP20
Protection class:	Class I
Power connection:	Fixed Power supply cord with safety plug
Cable length:	Approx. 0,4 m
Base:	E27
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Housing color:	Black
Dimensions:	Length: 23,5 cm Width: 14,5 cm Height: 21 cm
Weight:	530 g
Filter frame	
Outer diameter:	12,6 cm x 12,6 cm Ø 9,4 cm
Legal specifications	

OMNILUX PAR-30 230V SMD 11W E-27 LED 6500K

Operating voltage:	230 V, 220 - 240 V
Nominal wattage:	10 W
Base:	E27
Lamp type:	LED lamp; non-clear lamp; high voltage lamp; sealed beam lamp
Lamp specification:	Not dimmable Hot restrike
Beam angle:	50°
Color of light:	White
Color temperature:	6500K
Color rendering index (CRI) more than:	85 Ra
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Lamp life:	25000 h
Luminous flux:	1063 lm

Wavelength:	600 nm
Dimensions (LxD):	92x95 mm
Weight:	190 g
Legal specifications	
energy efficiency class (A - G):	E