



## Features:

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Suitable for different spot angles
- Small lighting-systems can also be realized with a small budget
- Control via plug and play
- With mounting bracket
- For PAR 30
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- <p>OMNILUX PAR-30 230V SMD 11W E-27 LED 6500K
- <h2 class="featureSatz">PAR-30 LED lamp</h2>Easy lamp replacement
- Energy-saving
- Hot restrike
- Easy installation
- Good color rendering index (CRI)

## Logistic

EAN / GTIN: 4026397403039  
Weight: 0,80 kg  
Length: 0.30 m  
Width: 0.22 m  
Heigh: 0.21 m

## Technical specifications:

Weight: 0.72 kg

Energy efficiency class (A - G): F

---

#### **EUROLITE PAR-30 Spot black**

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 100 W
Protection class:	Protection class I
Suitable lamp:	Max. 230 V/100 W E27
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0.75 mm <sup>2</sup> H05SS-F
Cable length:	Approx. 0.4 m
Base:	E27
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-30
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	12.8 cm x 12.8 cm
Dimensions:	Length: 23.5 cm Width: 14.5 cm Height: 21 cm
Weight:	0.53 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Color:	Black, matte
Shape:	Octagonal
Material:	Aluminum, 0.5 mm
Color:	Black, matte
Dimensions:	Length: 12.6 cm Width: 12.6 cm Diameter: Ø 9.4 cm
Weight:	0.022 kg

#### **OMNILUX PAR-30 230V SMD 11W E-27 LED 6500K**

Voltage (lamps):	230 V, AC
Nominal wattage:	11 W
Base:	E27
Lamp type:	LED lamp
Lamp specification:	Hot restrike
Beam angle:	50°
Setup:	Easy installation

Color of light:	White
Color temperature:	6500K
Color rendering index (CRI):	83 Ra
Lead time:	0.2 s
Construction:	PAR-30
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	20000 h
Luminous flux:	850 lm
Wavelength:	600 nm
Lamp current:	0.087 A
Dimensions (LxD):	92x95 mm
Weight:	0.19 kg
Energy efficiency class (A - G):	F
EPREL-Nr:	1016879

### Scope of delivery:

---

#### **1 x EUROLITE PAR-30 Spot black**

1 x spotlight  
1 x filter frame  
1 x user manual

#### **1 x OMNILUX PAR-30 230V SMD 11W E-27 LED 6500K**

1 x illuminant