



**The article is no longer in our assortment.**

### Features:

#### EUROLITE LED KLS Laser Bar FX Light Set

Bar with 2 derbies, 2 spots, white strobe LEDs, laser (RG, 2M), foot switch

- Crossbar with integrated DMX control unit and stand sleeve
- 2 laser diodes project hundreds of red and green laser beams
- 2 rotating derbies for mirror ball effects
- For application areas such as: Wedding/gala/events; mobile use; Party room; mobile djs / entertainer; small rental
- When fog is used, this effect becomes especially attractive
- 37 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Wireless footswitch; Master/slave function
- With Mounting bracket
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- Laser; multi beam effect; Strobe effect; flower effect
- Application possibility: On stand

#### **laser**

- Laser class 2M <BR> does not require additional protective measures or appointment of a laser safety officer

#### **spotlight**

- 3 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)<BR>2 spots controlled separately
- With a beam angle of 13°

#### **light effect**

### Logistic

- 3 powerful LEDs 1 W high-power R/G/B<BR>2 spots controlled separately  
**bar**
- 4 powerful LEDs 1 W high-power cold white (CW)<BR> LEDs controlled separately

**Package contents**

- 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x foot control, 1 x remote control, 2 x battery, 2 x mounting bracket, 2 x knurled screw, 1 x bag, 2 x washer

**OMNITRONIC Speaker System Stand alu bk**

High-quality speaker stand

- Stable speaker stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- Adjustable height

**Technical specifications:**

---

Weight: 12,50 kg

---

**EUROLITE LED KLS Laser Bar FX Light Set**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Device fuse:	5 x 20 mm, F 1 A Fuse replaceable
Lamp type:	LED lamp
Flash rate:	0 - 30 Hz
DMX channels:	3; 5; 9; 27
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone; Wireless footswitch; Master/slave function
Preprogrammed in:	Light ´J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Housing color:	Black
Attachment system:	2x Mounting bracket
Dimensions:	Width: 1,09 m Depth: 14,5 cm Height: 37 cm
Weight:	9,05 kg
Noise classification:	Class 2 (slight noise)

Laser

---

Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm Green (G) 30 mW 532nm
<b>Spotlight</b>	
LED:	3 x 3 W high-power 3in1 TCL RGB (homogenous color mix)
Beam angle:	13°
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	20°
<b>Light effect</b>	
LED:	3 x 1 W high-power R/G/B
<b>Bar</b>	
LED:	4 x 1 W high-power cold white (CW)
Beam angle (1/2 peak):	7°
<b>Foot control</b>	
Battery:	1 x 9.0 V E block 6LR61 alkaline manganese included
<b>Remote control</b>	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in

#### **OMNITRONIC Speaker System Stand alu bk**

Maximum carrying capacity:	30 kg
Height:	Maximum: 230 cm Minimum: 140 cm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Weight:	3,45 kg
Maximum load:	30 kg
Maximum load (DIN15560):	18 kg
Minimum height:	1.40 m
Maximum height:	2.20 m