



## Features:

### EUROLITE PAR-16 Spot MR-16 black

PAR-16 housing with GX-5.3 socket for 12 V MR-16 lamp

- Mini spots for 50 mm cool beam lamps
- Detailed original reconstruction of the big stage spots
- Ideal for decoration purposes
- Control via plug and play
- For PAR 16
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels
- Silent operation

### OMNILUX MR-16 12V GX-5,3 5W LED COB 3000K

Cool-beam mirrored lamp

- Different illumination angles for different application areas
- Low power consumption
- Powerful LED illuminant with COB (Chip on Board) technology
- A homogenous light blend is thereby guaranteed
- Comfortable warm white light
- Hot restrike
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Logistic

## Technical specifications:

---

Weight: 0.26 kg

---

### EUROLITE PAR-16 Spot MR-16 black

Power supply:	12V AC
Power consumption:	Max. 50 W
Protection class:	Protection class III
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0.25 m
Base:	GX5.3
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Housing color:	Black
Material:	Aluminum, 1 mm
Slot for spot length:	8 cm x 8 cm
Dimensions:	Length: 17 cm Width: 11 cm Height: 13 cm
Weight:	0.22 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Material:	Metal
Dimensions:	Length: 7.8 cm Width: 7.8 cm Diameter: Ø 5.3 cm
Weight:	0.026 kg

### OMNILUX MR-16 12V GX-5,3 5W LED COB 3000K

Voltage (lamps):	12 V, AC
Nominal wattage:	5 W
Base:	GX5.3
Lamp type:	LED lamp
Lamp specification:	Hot restrike
Beam angle:	36°
Color of light:	White
Color temperature:	3000K
Lead time:	1 s

Construction:	MR-16; reflector; bi pin
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	30000 h
Luminous flux:	350 lm
Wavelength:	592 nm
Lamp current:	0.72 A
Dimensions (LxD):	65x48 mm
Energy efficiency class (A++ - E):	A+

### **Scope of delivery:**

---

1 x spotlight  
1 x filter frame  
1 x user manual