



List price: 26.06 €

incl. 19% VAT.

Features:

EUROLITE PAR-20 Spot silver

PAR-20 housing with E-27 socket (with plug + cable)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Different spot angles, depending on lamp: spot (10°) or flood (30°)
- Strong cable tension relief
- Controlling by plug and play
- With Mounting bracket
- Available in various colors
- For PAR 20
- For application areas such as: Advertisement/Shop window; Decoration; Clubs/dancing school

Package contents

- 1 x spotlight, 1 x filter frame, 1 x user manual

Logistic

OMNILUX PAR-20 230V SMD 6W E-27 LED 6500K

PAR-20 lamp

- Color temperature 6500 K
- Stronger with the same power consumption
- Better brightness and color of light thanks to SMD LED
- Good color rendering index (CRI)
- For application areas such as: Clubs/dancing school; Stage

Technical specifications:

Weight:	420 g
Energy efficiency class (A - G):	F

EUROLITE PAR-20 Spot silver

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 75 W
IP classification:	IP20
Protection class:	Class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0,4 m
Base:	E27
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	8,4 cm x 8,4 cm
Dimensions:	Width: 15 cm Depth: 18 cm Height: 11,2 cm Diameter: Ø 8 cm
Weight:	320 g
Filter frame	
Material:	Aluminum
Dimensions:	Length: 8,4 cm Width: 8,4 cm Diameter: Ø 6,1 cm

OMNILUX PAR-20 230V SMD 6W E-27 LED 6500K

Operating voltage:	230 V
Nominal wattage:	6 W
Base:	E27
Lamp type:	LED lamp; clear lamp; high voltage lamp
Lamp specification:	Hot restrike; not dimmable
Beam angle:	50°
Color of light:	White
Color temperature:	6500K
Color rendering index (CRI):	81 Ra

Warm-up time:	0,2 s
Shape:	PAR-20
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	20000 h
Luminous flux:	510 lm
Wavelength:	662 nm
Dimensions (LxD):	86x64 mm
Weight:	100 g
Energy efficiency class (A - G):	F