

EUROLITE Set 4x LED SLS-603 + Case EC-SL4M size M

4x flat spotlight with 5 x 3 W 3in1 LED including practical flightcase

Art. No.: 20000306

GTIN:



List price: 522.41 €

incl. 19% VAT.

Features:

EUROLITE LED SLS-603 TCL + UV Floor

Flat spotlight with 5 x 3 W 3in1 LED (RGB) and one 3 W UV LED, incl. IR remote control

- Slim design for space-saving applications
- DMX and power terminals intelligently designed for easy wiring
- 6 powerful LEDs 3 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- UV effect; strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
- With a beam angle of 11°
- With double bracket
- 4 digit 7-segment LED display
- Preprogrammed in Light'J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; Colorchief
- Mains input and output for power linking up to 8 units
- Application possibility: Standing; suspended; on stand
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer

Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

Logistic

ROADINGER Flightcase EC-SL4M 4x SLS size M

Trunk case

- With 4 device compartments
- High-quality workmanship with plywood multi-layer glued 7 mm, dark brown, laminated
- Interior with felt cover
- Aluminum profile frames 30mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Rubber feet
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	14,06 kg
---------	----------

EUROLITE LED SLS-603 TCL + UV Floor

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	6 x 3 W high-power 4in1 QCL RGB/UV (homogenous color mix)
DMX channels:	4; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
Preprogrammed in:	Light´J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; Colorchief
Beam angle:	11°
Beam angle (1/2 peak):	11°
Beam angle (1/10 peak):	28°
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Plastic; metal; ABS Acrylonitrile butadiene styrene
Dimensions:	Width: 23 cm Depth: 11 cm Height: 23 cm
Weight:	1,41 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0

Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1,1 m
Mounting bracket	
Diameter mounting holes:	5 x Ø11mm
Material:	Metal, 2 mm
Color:	Black
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase EC-SL4M 4x SLS size M

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Transport aid:	Rubber feet
Material:	Plywood multi-layer glued, 7 mm
Color:	Dark brown, laminated; black, laminated
Compartment dimensions:	11,5 cm x 24,5 cm x 34 cm
Inside dimensions:	49 cm x 25 cm x 39 cm
Dimensions:	Width: 52,5 cm
	Depth: 28,5 cm
	Height: 44,5 cm
Weight:	8,40 kg