

## EUROLITE Set 4x LED SLS-603 + Case EC-SL4M size M

4x flat spotlight with 5 x 3 W 3in1 LED including practical flightcase

Art. No.: 2000306

GTIN: 4026397601183



### Features:

- Slim design for space-saving applications
- DMX and power terminals intelligently designed for easy wiring
- 6 LEDs 3 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- UV effect; strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
- Fixtures available for Light'J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; Colorchief
- With a beam angle of 11°
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Application possibility: Standing; suspended; on stand
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels
- <p>ROADINGER Flightcase EC-SL4M 4x SLS size M
- <h2 class="featureSatz">Trunk case</h2>With 4 device compartments
- High-quality workmanship with plywood multi-layer glued 7 mm, dark brown, laminated
- Interior with felt cover
- Aluminum profile frames 30mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock

### Logistic

EAN / GTIN: 4026397601183

Weight: 15,78 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

- Rubber feet
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight:	14.04 kg
---------	----------

---

### EUROLITE LED SLS-603 TCL + UV Floor

Power supply:	100-240 V AC, 50/60 Hz
---------------	------------------------

---

Power consumption:	20 W
--------------------	------

---

IP classification:	IP20
--------------------	------

---

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
-------------------	--

---

Power output:	1 x IEC connector (F) mounting version
---------------	--

---

Lamp type:	LED lamp
------------	----------

---

LED type:	6 x 3 W high-power 4in1 QCL RGB/UV (homogenous color mix)
-----------	---

---

DMX channels:	4; 8
---------------	------

---

DMX input:	1 x 3-pin XLR (M) mounting version
------------	------------------------------------

---

DMX output:	1 x 3-pin XLR (F) mounting version
-------------	------------------------------------

---

Cooling:	1 x cooling fan
----------	-----------------

---

Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
----------	---

---

Fixtures available for:	Light J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; Colorchief
-------------------------	--

---

Beam angle:	11°
-------------	-----

---

Beam angle (1/2 peak):	11°
------------------------	-----

---

Beam angle (1/10 peak):	28°
-------------------------	-----

---

Housing color:	Black
----------------	-------

---

Attachment system:	Double bracket
--------------------	----------------

---

Display type:	4 digit 7-segment LED display
---------------	-------------------------------

---

Material:	Plastic; metal; ABS Acrylonitrile butadiene styrene
-----------	---

---

Dimensions:	Width: 23 cm Depth: 11 cm Height: 23 cm
-------------	---

---

Weight:	1.41 kg
---------	---------

---

Noise classification:	Class 2 (slight noise)
-----------------------	------------------------

---

Photobiological safety:	Risk Group 0
-------------------------	--------------

---

Cable construction:	3 x 0.75 mm <sup>2</sup> H05VV-F
---------------------	----------------------------------

---

Cable length:	Approx. 1.1 m
---------------	---------------

---

Diameter mounting holes:	5 x Ø11mm
--------------------------	-----------

---

Material:	Metal, 2 mm
-----------	-------------

---

Color:	Black
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **ROADINGER Flightcase EC-SL4M 4x SLS size M**

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Transport aid:	Rubber feet
Material:	Plywood multi-layer glued, 7 mm
Color:	Dark brown, laminated; black, laminated
Compartment dimensions:	11.5 cm x 24.5 cm x 34 cm
Inside dimensions:	49 cm x 25 cm x 39 cm
Dimensions:	Width: 52.5 cm Depth: 28.5 cm Height: 44.5 cm
Weight:	8.40 kg

#### **Scope of delivery:**

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual