

EUROLITE Set 4x LED SLS-180 + Case EC-SL4M size M

4x flat spotlight with 18 x 1 W LED including practical flightcase

Art. No.: 20000307 GTIN:







The article is no longer in our assortment.

Features: Logistic

EUROLITE LED SLS-180 RGB 18x1W Floor

Flat spotlight with 18 x 1 W LED in R, G, B

- Equipped with 18 x 1 W LED: 6 x red, 6 x green, 6 x blue
- Flat housing form requires minimal space when rigging
- Second mounting bracket for safe standing installation
- Additional rubber feet when the spot shall be positioned on the floor without mounting bracket
- Comfortable addressing and setting via control panel with LED display
- Functions: Static colors, three different color changes (2 x FC*, 1 x SC+) with adjustable speed, RGB color mixture, strobe effect, dimmer
- * FC = Fading Colors: uninterruptedly gradually fades out colors in a given period of time
- + SC = Switching Colors: uninterruptedly switches color in a given period of time
- Memory function
- Master/Slave for parallel operation of several devices
- IEC terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 18 powerful LEDs 1 W high-power R/G/B (homogenous color mix)
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4;
 LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- With a beam angle of 35°
- 4 digit 7-segment LED display

Package contents

- 1 x spotlight, 1 x power cord, 1 x user manual

ROADINGER Flightcase EC-SL4M 4x SLS size M

Trunk case

- With 4 device compartments
- High-quality workmanship with plywood multi-layer glued 7 mm, dark brown, laminated
- Interior with felt cover
- Aluminum profile frames 30mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Rubber feet
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 13,38 kg

EUROLITE LED SLS-180 RGB 18x1W Floor

| Power supply: | 100-240 V AC, 50/60 Hz |
|------------------------|--|
| Power consumption: | 12,00 W |
| IP classification: | IP20 |
| Protection class: | Protection class II |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Cable length: | 1,4 m |
| Power output: | 1 x IEC connector (F) mounting version |
| Lamp type: | LED lamp |
| LED type: | 18 x 1 W high-power R/G/B (homogenous color mix) |
| DMX channels: | 3; 5; 7 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | Stand-alone; DMX; sound to light via microphone |
| Preprogrammed in: | Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain |
| Beam angle: | 35° |
| Beam angle (1/2 peak): | 35° |
| Housing color: | Black |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Width: 21 cm Depth: 10,5 cm Height: 22 cm |
| Weight: | 1,25 kg |
| · | |

| Noise classification: | Class 2 (slight noise) |
|-----------------------|--|
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase EC-SL4M 4x SLS size M

| Maximum load: | 25 kg |
|--------------------------|---|
| Aluminum profile frames: | 30 mm |
| Case handle: | 1 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 1 pc/pcs |
| Transport aid: | Rubber feet |
| Material: | Plywood multi-layer glued, 7 mm |
| Color: | Dark brown, laminated; black, laminated |
| Compartment dimensions: | 11,5 cm x 24,5 cm x 34 cm |
| Inside dimensions: | 49 cm x 25 cm x 39 cm |
| Dimensions: | Width: 52,5 cm |
| | Depth: 28,5 cm |
| | Height: 44,5 cm |
| Weight: | 8,40 kg |