# eurolite®

# EUROLITE Set 4x AKKU TL-3 TCL + Case with charging function







# The article is no longer in our assortment.

# Features:

### EUROLITE AKKU TL-3 TCL Trusslight

Spotlight with 3 x 3 W 3in1 LED (RGB) for lighting within trussing

- Compact and bright, making it perfect for truss installation
- Cordless, flexible and versatile
- Equipped with 3 x 3 W TCL LED in red, green and blue
- Operation via mains connection or built-in rechargeable lithium-ion battery with up to 6.5 hours operating time
- Integrated automatic charging of the battery with indicator
- Controllable via EUROLITE IR-7 remote control; included in the delivery
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 3, 5 or 8 DMX channels selectable
- Functions: static colors, stepless RGB color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control, Master/Slave operation
- Dimmer speed (step response) adjustable
- Adjustable microphone sensitivity
- Addressing via control panel with 4-digit LED display
- Ideal for booth construction, stages and any kind of truss
- Ideal for ALUTRUSS 3-POINT SYSTEM DECOLOCK DQ3
- Hanging as well as standing installation possible
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included power cable with safety power plug
- Feed-through output allows to power up to 8 devices
- 3 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)
- Control via DMX; stand-alone; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain
- Flicker-free

# Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- With a beam angle of 16° device
- Cordless, flexible and versatile
- Battery operation up to 6,5h depending on program used Package contents
- 1 x device, 1 x remote control

#### ROADINGER Flightcase 4x AKKU TL-3 Trusslight QuickDMX with charging function

Trunk case

- With 4 device compartments
- With accessory compartment
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- For further information about this product, please refer to the Data Sheet under "Downloads" Package contents
- 1 x device, 1 x power cord, 1 x user manual

#### **Technical specifications:**

Weight:

14,50 kg

#### EUROLITE AKKU TL-3 TCL Trusslight

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	19,00 W
IP classification:	IP20
Power connection:	Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	3 x 3 W high-power 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 30 Hz
DMX channels:	3; 5; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; stand-alone; sound to light via microphone
Preprogrammed in:	Light'J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	34°
Housing color:	Black

Dimensions:	Width: 12,1 cm Depth: 10,8 cm
	Height: 13,6 cm
Weight:	1,35 kg
Device	
Battery pack type:	1 x lithium ion 11,1 V, 4400 mAh, 48,84 Wh
Battery pack:	Battery operation up to 6,5h depending on program used
	Recharging time 4,5h
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## ROADINGER Flightcase 4x AKKU TL-3 Trusslight QuickDMX with charging function

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 1150 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 5 A fuse replaceable
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Material:	Plywood multi-layer glued, 9 mm
Color:	Black, laminated
Compartment dimensions:	15,5 cm x 15,5 cm x 11,5 cm
Accessory compartment:	9 cm x 34 cm x 11,5 cm
Dimensions:	Width: 57 cm
	Depth: 37 cm
	Height: 24,5 cm
Weight:	9,10 kg