

EUROLITE Set 4x LED PAR-56 HCL Short sil + EPS Case

4x PAR-56 Spot with 9 x 10W 6in1 LED and RGBAW+UV color mixing including flightcase

Art. No.: 20000325

GTIN:



The article is no longer in our assortment.

Features:

EUROLITE LED PAR-56 HCL Short sil

PAR-56 spot with 9 x 10 W 6in1 LED and RGBAW+UV color mixing

- Stepless color blend, color change, dimmer, strobe effect and UV effect
- 9 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- Control via stand-alone; DMX; sound to light via microphone; IR remote control
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; LED EASY OPERATOR 4x4; Light Captain
- Flicker-free
- With a beam angle of 20°
- With mounting bracket
- 4 digit 7-segment LED display
- Available in various colors

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Logistic

ROADINGER Flightcase EPS-56 4x PAR-56 Spot short

Trunk case

- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks

- 1 high-quality butterfly lock
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	15,10 kg
EUROLITE LED PAR-56 HCL Short sil	
Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	9 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	4; 6; 10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; sound to light via microphone; IR remote control
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; LED EASY OPERATOR 4x4; Light Captain
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	38°
Housing color:	Silver
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 20,5 cm Depth: 17,5 cm Height: 23 cm
Weight:	1,79 kg
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	22 cm x 22 cm x 24 cm
Inside dimensions:	44 cm x 44 cm x 24 cm
Dimensions:	Width: 48,5 cm Depth: 48,5 cm Height: 31 cm
Weight:	7,95 kg