

EUROLITE Set 4x LED PAR-56 HCL Short sw + PRO Case

4x PAR-56 Spot with 9 x 10W 6in1 LED and RGBAW+UV color mixing including PRO flightcase

Art. No.: 20000326

GTIN:







The article is no longer in our assortment.

Features: Logistic

EUROLITE LED PAR-56 HCL Short bl

PAR-56 spot with 9 x 10 W 6in1 LED and RGBAW+UV color mixing

- 9 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect; UV effect
- The device is cooled by low-noise cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone; IR remote control
- Flicker-free
- With a beam angle of 20°
- With Mounting bracket
- 4 digit 7-segment LED display
- Available in various colors
- Preprogrammed in Light 'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6;
 LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- For application areas such as: Clubs/dancing school; Party room; Stage; restaurants, bars and hotels
- Application possibility: Suspended; on stand

Package contents

1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

ROADINGER Flightcase 4x PAR-56 Spot short

PRO flightcase for 4 x PAR-56 spotlight

- Detachable compartments case can also be used as universal transport case
- With 4 Device compartments

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 14,75 kg

EUROLITE LED PAR-56 HCL Short bl

Power supply:	100-240 V AC, 50/60 Hz	
Power consumption:	75 W	
IP classification:	IP20	
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)	
Fuse:	5 x 20 mm, F 1 A Fuse replaceable	
Lamp type:	LED lamp	
LED:	9 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)	
DMX channels:	4; 6; 10	
DMX input:	3-pin XLR (M) mounting version	
DMX output:	3-pin XLR (F) mounting version	
Cooling:	1 x low-noise cooling fan	
Control:	Stand-alone; DMX; Sound to light via Microphone; IR remote control	
Preprogrammed in:	Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3	
Projection:	Flicker-free	
Beam angle:	20°	
Beam angle (1/2 peak):	20°	
Beam angle (1/10 peak):	38°	
Housing color:	Black	
Attachment system:	Mounting bracket	
Display type:	4 digit 7-segment LED display	
Dimensions:	Width: 20,5 cm Depth: 17,5 cm Height: 23 cm	
Weight:	1,79 kg	
Photobiological safety:	Risk Group 0	

Ren	note	cor	tro
1101	IULE	COL	ıuc

Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x PAR-56 Spot short

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	21,5 cm x 21,5 cm x 23 cm
Inside dimensions:	43 cm x 43 cm x 23 cm
Dimensions:	Width: 48,5 cm
	Depth: 48,5 cm
	Height: 31 cm
Weight:	7,60 kg