

EUROLITE Party Set 3

Art. No.: 20000332

GTIN:



The article is no longer in our assortment.

| Features: | Logistic |
|-----------|----------|

EUROLITE LED Mini D-5 Beam Effect

Mini beam effect with LEDs in R, G, B, and W

- 24 lenses fill the room with moving colorful beams
- Practicle size, easily transportable
- 6 powerful LEDs 3 W high-power R/G/B/W/A
- Color macros changing
- Flower effect
- The device is cooled by passive convection cooling
- Control via stand-alone; sound to light via microphone
- With mounting bracket
- For application areas such as: Party room; small rental
- Very quiet working noise
- Application possibility: Suspended; on stand

Package contents

- 1 x light effect, 1 x power cord, 1 x user manual

EUROLITE LED PARty TCL Spot

Compact spotlight with 12 x 3 W 3in1 TCL RGB LED and DMX control

- 12 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)
- Color change programs; color blend stepless; pulse effect adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 18 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone

- Preprogrammed in LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light'J; Colorchief
- Flicker-free
- With a beam angle of 17°
- With mounting bracket
- 4 digit 7-segment LED display
- For application areas such as: Party room; small rental
- Application possibility: Suspended; on stand

Package contents

1 x light effect, 1 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x user manual

EUROLITE LED Party UV Bar-9

Simple UV lighting bar with 9 x 1 W ultra violet (UV) LED

- Perfect for decorative and illumination purposes
- Slender housing
- 9 powerful LEDs 1 W high-power ultra violet (UV)
- UV effect
- The device is cooled by passive convection cooling
- Control via on/off switch at cable
- With a beam angle of 30°
- With mounting bracket
- Various versions available
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended; standing

Package contents

- 1 x spotlight, 2 x mounting bracket, 1 x user manual

EUROLITE LED Party strobe 36

Ultra compact party strobe with high-power LEDs

- Stroboscope with 36 white SMD 5050 LEDs
- Perfect for decorations or party rooms
- Smallest dimensions, low weight
- Auto and sound mode selectable
- Built-in microphone with sensitivity control
- Variable flash rate: 1-8 flashes/second
- Low price, portable and user-friendly
- 36 powerful LEDs SMD 5050 cold white (CW)
- Strobe effect
- Control via stand-alone

EUROLITE N-10 Fog Machine black

400 watt fogger with remote control

- Output distance: Approx. 2 m
- With level indication
- Operates on water-based fluid
- Control via wired remote control
- With mounting bracket
- For application areas such as: Party room; clubs/dancing school; small rental
- Application possibility: Standing; suspended

Package contents

 1 x device, 1 x user manual, 1 x power cord, 1 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x filter

EUROLITE Smoke Fluid -A2D- Action Smoke Fluid 1I

Fog effect with low density and hang time

- Odorless
- Glycerine- and DEG-free composition
- Non-toxic

- Not harmful to health
- Biodegradable according to OECD 301E/EEC 84/449 C3
- Non-flammable, no transport restrictions, no hazardous material
- Permanent quality control
- Proven quality
- Water-based fluid ready for use
- Made in Europe
- For application areas such as: Wedding/gala/events; small rental; party room; clubs/dancing school

Technical specifications:

Weight: 6,54 kg

EUROLITE LED Mini D-5 Beam Effect

| Power supply: | 100-240 V AC, 50/60 Hz |
|--------------------------|--|
| Power consumption: | 20 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug included |
| Lamp type: | LED lamp |
| LED type: | 6 x 3 W high-power R/G/B/W/A |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; sound to light via microphone |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Material: | Metal |
| Dimensions: | Width: 21 cm |
| | Depth: 19,5 cm |
| | Height: 20,5 cm |
| Weight: | 1,95 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise- sensitive environments) |
| Power cord | |
| Cable construction: | 3 x 0,75 mm² H05VV-F |
| Cable length: | Approx. 1,2 m |
| Mounting bracket | |
| Diameter mounting holes: | 1 x Ø11mm |
| Material: | Metal, 2 mm |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUROLITE LED PARty TCL Spot

| Power consumption: IP classification: IP classification: IP classification: Protection class: Protection class II Power connection: Example (a) September 1 (a) September 2 (a) Septemb | Power supply: | 100-240 V AC, 50/60 Hz |
|--|--|---|
| Protection class: Protection class II Power connection: Fixed power supply cord with Euro plug Cable construction: 2 x 0,75 mm² H03VVH2-F Lamp type: LED lamp LED type: 12 x 3 W high-power 3in1 TCL RGB (homogenous color mix) Flash rate: 0,5 - 16 Hz DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: LED PC-Control 512; LED EASY OPERATOR 444; LED EASY OPERATOR 444; LED EASY OPERATOR 344; LED EASY OPERATOR 344; LED EASY OPERATOR 344; LED EASY OPERATOR 344; LED EASY OPERATOR 346; LE | | |
| Power connection: Cable construction: 2 x 0,75 mm² H03VVH2-F LED lamp LED type: 12 x 3 W high-power 3in1 TCL RGB (homogenous color mix) Flash rate: 0,5 - 16 Hz DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR Ax6; LED EASY OPERATOR DELUXE; Light Captain; Light' J; Colorchief Projection: Flicker-free PWM frequency: 15700 Hz Beam angle: 17° Beam angle: 17° Beam angle: 17° Beam angle (1/12 peak): 17° Beam angle (1/10 peak): 4 digit 7-segment LED display Dimensions: Width: 15 cm Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | IP classification: | IP20 |
| Cable construction: 2 x 0,75 mm² H03VVH2-F Lamp type: LED lamp LED type: 12 x 3 W high-power 3in1 TCL RGB (homogenous color mix) Flash rate: 0,5 - 16 Hz DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR 4x6; LED EASY OPERATOR 2x6; LED E | Protection class: | Protection class II |
| LED type: LED type: 12 x 3 W high-power 3in1 TCL RGB (homogenous color mix) Flash rate: 0,5 - 16 Hz DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light 'J; Colorchief Projection: Flicker-free PWM frequency: 15700 Hz Beam angle: 17° Beam angle (1/10 peak): 38° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Width: 15 cm Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metail, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | Power connection: | Fixed power supply cord with Euro plug |
| LED type: 12 x 3 W high-power 3in1 TCL RGB (homogenous color mix) Flash rate: 0,5 - 16 Hz DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR 2 ELUXE; Light Captain; Light J; Colorchief Projection: Flicker-free PWM frequency: 15700 Hz Beam angle: 17° Beam angle (1/12 peak): 17° Beam angle (1/10 peak): 38° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Width: 15 cm Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | Cable construction: | 2 x 0,75 mm² H03VVH2-F |
| (homogenous color mix) Flash rate: 0,5 - 16 Hz DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR EASY OPERATOR EASY OPERATOR DELUXE; Light Captain; Light 'J; Colorchief Projection: Flicker-free PWM frequency: 15700 Hz Beam angle: 17° Beam angle (1/10 peak): 17° Beam angle (1/10 peak): 38° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Width: 15 cm | Lamp type: | LED lamp |
| DMX channels: DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: LED PC-Control 512; LED EASY OPERATOR 444; LED EASY OPERATOR 4x6, LED EASY OPERATOR DELUXE; Light Captain; Light'J; Colorchief Projection: Flicker-free PWM frequency: 15700 Hz Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): 38° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Width: 15 cm Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | LED type: | • . |
| DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light'J; Colorchief Projection: Flicker-free PWM frequency: 15700 Hz Beam angle: 17° Beam angle (1/12 peak): 17° Beam angle (1/10 peak): 4 digit 7-segment LED display Dimensions: Width: 15 cm Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | Flash rate: | 0,5 - 16 Hz |
| DMX output: 3-pin XLR (F) mounting version 1 x cooling: 1 x cooling fan Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light'J; Colorchief Projection: Flicker-free PWM frequency: 15700 Hz Beam angle: 17° Beam angle (1/12 peak): 17° Beam angle (1/10 peak): 38° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Width: 15 cm Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | DMX channels: | 5 |
| Cooling: Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light'J; Colorchief Projection: Flicker-free PWM frequency: 15700 Hz Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): Beam angle (1/10 peak): Beam angle (1/10 peak): Wounting bracket Display type: 4 digit 7-segment LED display Dimensions: Width: 15 cm Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | DMX input: | 3-pin XLR (M) mounting version |
| Control: Stand-alone; DMX; sound to light via microphone Preprogrammed in: LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light 'J; Colorchief Projection: Flicker-free PWM frequency: 15700 Hz Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): 38° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Width: 15 cm Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | DMX output: | 3-pin XLR (F) mounting version |
| Preprogrammed in: LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light'J; Colorchief Projection: Flicker-free PWM frequency: 15700 Hz Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): Beam angle (1/10 peak): Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Width: 15 cm Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | Cooling: | 1 x cooling fan |
| 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light J; Colorchief Projection: Flicker-free PWM frequency: 15700 Hz Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): 38° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Width: 15 cm Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | Control: | Stand-alone; DMX; sound to light via microphone |
| PWM frequency: Beam angle: 17° Beam angle (1/2 peak): Housing color: Attachment system: Display type: 4 digit 7-segment LED display Dimensions: Width: 15 cm Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | Preprogrammed in: | 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light'J; |
| Beam angle: 17° Beam angle (1/2 peak): 17° Beam angle (1/10 peak): 38° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Width: 15 cm | Projection: | Flicker-free |
| Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Width: 15 cm Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | | |
| Beam angle (1/10 peak): Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Width: 15 cm Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | | 15700 Hz |
| Housing color: Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Dimensions: Width: 15 cm Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | PWM frequency: | |
| Attachment system: Display type: 4 digit 7-segment LED display Dimensions: Width: 15 cm Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | PWM frequency: Beam angle: | 17° |
| Display type: Display type: Vidth: 15 cm Depth: 9 cm Height: 16 cm Weight: O,43 kg Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | PWM frequency: Beam angle: Beam angle (1/2 peak): | 17° 17° |
| Dimensions: Width: 15 cm Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | PWM frequency: Beam angle: Beam angle (1/2 peak): Beam angle (1/10 peak): | 17° 17° 38° |
| Depth: 9 cm Height: 16 cm Weight: 0,43 kg Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | PWM frequency: Beam angle: Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: | 17° 17° 38° Black |
| Noise classification: Class 2 (slight noise) Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | PWM frequency: Beam angle: Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Attachment system: | 17° 17° 38° Black Mounting bracket |
| Mounting bracket Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | PWM frequency: Beam angle: Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Attachment system: Display type: | 17° 17° 38° Black Mounting bracket 4 digit 7-segment LED display Width: 15 cm Depth: 9 cm |
| Diameter mounting holes: 1 x Ø12mm; 2 x Ø8mm Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | PWM frequency: Beam angle: Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Attachment system: Display type: Dimensions: | 17° 17° 38° Black Mounting bracket 4 digit 7-segment LED display Width: 15 cm Depth: 9 cm Height: 16 cm |
| Material: Metal, 1 mm, painted Color: Black, matte Legal specifications Special product: Not designed for household room illumination | PWM frequency: Beam angle: Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Attachment system: Display type: Dimensions: | 17° 17° 38° Black Mounting bracket 4 digit 7-segment LED display Width: 15 cm Depth: 9 cm Height: 16 cm 0,43 kg |
| Color: Black, matte Legal specifications Special product: Not designed for household room illumination | PWM frequency: Beam angle: Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Attachment system: Display type: Dimensions: Weight: Noise classification: | 17° 17° 38° Black Mounting bracket 4 digit 7-segment LED display Width: 15 cm Depth: 9 cm Height: 16 cm 0,43 kg |
| Legal specifications Special product: Not designed for household room illumination | PWM frequency: Beam angle: Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Attachment system: Display type: Dimensions: Weight: Noise classification: Mounting bracket | 17° 17° 38° Black Mounting bracket 4 digit 7-segment LED display Width: 15 cm Depth: 9 cm Height: 16 cm 0,43 kg Class 2 (slight noise) |
| Special product: Not designed for household room illumination | PWM frequency: Beam angle: Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Attachment system: Display type: Dimensions: Weight: Noise classification: Mounting bracket Diameter mounting holes: | 17° 17° 38° Black Mounting bracket 4 digit 7-segment LED display Width: 15 cm Depth: 9 cm Height: 16 cm 0,43 kg Class 2 (slight noise) 1 x Ø12mm; 2 x Ø8mm |
| | PWM frequency: Beam angle: Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Attachment system: Display type: Dimensions: Weight: Noise classification: Mounting bracket Diameter mounting holes: Material: | 17° 17° 38° Black Mounting bracket 4 digit 7-segment LED display Width: 15 cm Depth: 9 cm Height: 16 cm 0,43 kg Class 2 (slight noise) 1 x Ø12mm; 2 x Ø8mm Metal, 1 mm, painted |
| Intended use: Show effect lighting | PWM frequency: Beam angle: Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Attachment system: Display type: Dimensions: Weight: Noise classification: Mounting bracket Diameter mounting holes: Material: Color: | 17° 17° 38° Black Mounting bracket 4 digit 7-segment LED display Width: 15 cm Depth: 9 cm Height: 16 cm 0,43 kg Class 2 (slight noise) 1 x Ø12mm; 2 x Ø8mm Metal, 1 mm, painted |
| | PWM frequency: Beam angle: Beam angle (1/2 peak): Beam angle (1/10 peak): Housing color: Attachment system: Display type: Dimensions: Weight: Noise classification: Mounting bracket Diameter mounting holes: Material: Color: Legal specifications | 17° 17° 38° Black Mounting bracket 4 digit 7-segment LED display Width: 15 cm Depth: 9 cm Height: 16 cm 0,43 kg Class 2 (slight noise) 1 x Ø12mm; 2 x Ø8mm Metal, 1 mm, painted Black, matte |

EUROLITE LED Party UV Bar-9

Power supply: 100-240 V AC, 50/60 Hz

| Power consumption: | 20 W |
|--------------------------|--|
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Cable length: | Approx. 1 m |
| Lamp type: | LED lamp |
| LED type: | 9 x 1 W high-power ultra violet (UV) |
| Cooling: | Passive convection cooling |
| Control: | On/off switch at cable |
| Beam angle: | 30° |
| Beam angle (1/2 peak): | 30° |
| Wavelength: | 398 nm |
| Housing color: | Black matte |
| Attachment system: | 2x mounting bracket |
| Material: | Metal |
| Dimensions: | Length: 50 cm |
| | Depth: 6,5 cm |
| | Height: 6,5 cm |
| Weight: | 0,66 kg |
| Noise classification: | Class 0 (no noise at all) |
| Photobiological safety: | Risk Group 0 at 1 m |
| Mounting bracket | |
| Diameter mounting holes: | 1 x Ø10mm; 1 x Ø6mm |
| Material: | Aluminum, 2 mm |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |
| | |

EUROLITE LED Party strobe 36

| Power supply: | 230 V AC, 50 Hz |
|------------------------|--|
| Power consumption: | 12 W |
| Power connection: | Fixed power supply cord with Euro plug |
| Cable length: | 1 m |
| Lamp type: | LED lamp |
| LED type: | 36 x SMD 5050 cold white (CW) |
| Flash rate: | 1 - 8 Hz |
| Control: | Stand-alone |
| Beam angle (1/2 peak): | 80° |
| Color temperature: | 6500K |
| Dimensions: | Width: 10 cm |
| | Depth: 11 cm |
| | Height: 10 cm |
| Weight: | 0,20 kg |
| Legal specifications | |

| Special product: | Not designed for household room illumination |
|------------------|--|
| Intended use: | Show effect lighting |

EUROLITE N-10 Fog Machine black

| 230 V AC, 50 Hz |
|---|
| 400 W |
| IP20 |
| Mains input via IEC connector (M) mounting version power supply cord with safety plug |
| Approx. 5 min |
| Approx. 2 m |
| 0,3 I water-based fluid fixed tank |
| Approx. 21 ml/min |
| Wired remote control |
| Black |
| Mounting bracket |
| 400 W |
| Overheat |
| Black |
| Width: 14,5 cm |
| Depth: 26,5 cm |
| Height: 17 cm |
| 1,87 kg |
| Class 3 (clearly perceptible sounds) |
| |

EUROLITE Smoke Fluid -A2D- Action Smoke Fluid 1I

| Container size: | 11 |
|-----------------|---------------------------------|
| Type of fluid: | Water-based fluid ready for use |
| Weight: | 1,00 kg |