

EUROLITE Set 4x LED THA-100F Theater-Spot + Case

4x Fresnel spot, 100 W warm white LED, extremely quiet, DMX including PRO flightcase

Art. No.: 20000361

GTIN:



The article is no longer in our assortment.

Features:

EUROLITE LED THA-100F Theatre-Spot

Fresnel spotlight (fresnel lens), 100 W warm white LED, extremely quiet, DMX

- Light impression of a conventional 750 W lamp
- 1 powerful LED 100 W COB (chip-on-board) warm white (WW)
- Zoom manual
- Dimmer electronic; dimmer curves adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via DMX
- Preprogrammed in LED PC-Control 512; Light'J; Light Captain
- Flicker-free
- With a beam angle of 10° - 60°
- With mounting bracket
- LCD display
- Mains input and output for power linking up to 8 units

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x filter frame

Logistic

ROADINGER Flightcase 4x LED THA-100F/THA-120PC with wheels

Trunk case with castors, PRO version

- With accessory compartment
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding

- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	56,00 kg
---------	----------

EUROLITE LED THA-100F Theatre-Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	120 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray)
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) warm white (WW)
Equipment:	Zoom manual
DMX channels:	1; 3
Cooling:	Temperature-controlled fan
Control:	DMX
Preprogrammed in:	LED PC-Control 512; Light'J; Light Captain
Projection:	Flicker-free
Beam angle:	10° - 60°
Beam angle (1/2 peak):	10 - 50°
Beam angle (1/10 peak):	12 - 60°
Color temperature:	3200K
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Length: 37 cm Width: 33,5 cm Height: 26,5 cm
Weight:	6,30 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED THA-100F/THA-120PC with wheels

Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Middle compartment:	10,5 cm x 59 cm x 40,5 cm
Outer compartment:	33 cm x 29,5 cm x 40,5 cm
Inside dimensions:	76,5 cm x 59 cm x 40,5 cm
Dimensions:	Width: 82 cm Depth: 65,5 cm Height: 67,5 cm
Weight:	27,60 kg