

EUROLITE Set 4x LED THA-100F MK2 Theater-Spot + Case

Art. No.: 2000363

4x Fresnel spot, 100 W warm white LED, CRI >90, quiet, DMX including PRO flightcase

GTIN:



List price: 2438.31 €

incl. 19% VAT.

Features:

EUROLITE LED THA-100F MK2 Theater-Spot

Fresnel spotlight (fresnel lens), 100 W warm white LED, CRI >90, quiet, DMX

- Color temperature 3200 K
- Stand-alone or DMX mode
- Electronic dimmer (0-100%)
- Various dimmer curves selectable
- Strobe effect
- With color filter frame
- Optional barndoors available
- Mains input and output for power linking up to 8 units
- 1 powerful LED 100 W COB (chip-on-board) warm white (WW)
- Can be operated in 1; 3 CH mode
- The device is cooled by super silent fan
- Controlling by stand-alone; DMX
- Preprogrammed in LED PC-Control 512; Light Captain
- With a beam angle of 6 - 46°
- Very high color rendering index (CRI)
- With Mounting bracket
- LCD display for easy controlling

Logistic

ROADINGER Flightcase 4x LED THA-100F/THA-120PC with wheels

PRO flightcase for 4 x LED THA-100F or LED THA-120PC

- With accessory compartment
- With 4 Device compartments

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- With 4 castors with 2 locking brakes
- With 4 built-in stacking trays in the cover
- Made in Europe

Technical specifications:

Weight: 55,80 kg

EUROLITE LED THA-100F MK2 Theater-Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	120 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
Lamp type:	LED lamp
LED:	1 x 100 W COB (chip-on-board) warm white (WW)
Color temperature:	3200K
Equipment:	Zoom manual
DMX channels:	1; 3
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	Super silent fan
Control:	Stand-alone; DMX; LED PC-Control 512; Light Captain
Beam angle:	6 - 46°
Beam angle (1/2 peak):	6 - 31°
Beam angle (1/10 peak):	22 - 46°
Color rendering index (CRI) more than:	90 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Length: 37 cm Width: 33,5 cm Height: 26,5 cm
Weight:	6,30 kg
Noise classification:	Class 2 (slight noise)

Legal specifications

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED THA-100F/THA-120PC with wheels

Aluminum profile frames:	25 mm
Case handles:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Middle compartment:	10,5 cm x 59 cm x 40,5 cm
Outer compartment:	33 cm x 29,5 cm x 40,5 cm
Inside dimensions:	76,5 cm x 59 cm x 40,5 cm
Dimensions:	Width: 82 cm Depth: 65,5 cm Height: 67,5 cm
Weight:	27,60 kg
