

EUROLITE Set 2x LED THA-120PC Theater-Spot + Case

2x Fresnel spot, 120 W COB LED (RGBW), extremely quiet, DMX including PRO flightcase

Art. No.: 2000364

GTIN:



List price: 1724.31 €

incl. 19% VAT.

Features:

EUROLITE LED THA-120PC Theater-Spot

Fresnel spotlight (fresnel lens), 120 W COB LED (RGBW), extremely quiet, DMX

- Dimmer speed (step response) adjustable
- Electronic dimmer (0-100%)
- Color change, color fade and strobe effect with variable speed
- With color filter frame
- Compact design
- Mains input and output for power linking up to 8 units
- 1 powerful LED 120 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Can be operated in 4; 6; 7 CH mode
- The device is cooled by temperature-controlled fan
- Controlling by stand-alone; DMX; Sound to light via Microphone
- Preprogrammed in LED PC-Control 512; Light J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- Flicker-free
- With a beam angle of 3° - 43°
- With Mounting bracket

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x filter frame

ROADINGER Flightcase 2x LED THA-100F/THA-120PC

PRO flightcase for 2 x THA-100/120

- With accessory compartment
- With 2 Device compartments

Logistic

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 25,30 kg

EUROLITE LED THA-120PC Theater-Spot

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 135 W |
| IP classification: | IP20 |
| Power connection: | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x PowerCON (gray), mounting version |
| LED: | 1 x 120 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix) |
| DMX channels: | 4; 6; 7 |
| DMX input: | 1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | Stand-alone; DMX; Sound to light via Microphone; LED PC-Control 512; Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain |
| Beam angle: | 3° - 43° |
| Beam angle (1/2 peak): | 3 - 32° |
| Beam angle (1/10 peak): | 9 - 43° |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Dimensions: | Length: 37 cm Width: 25,6 cm Depth: 36 cm |
| Weight: | 5,85 kg |
| Noise classification: | Class 2 (slight noise) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 2x LED THA-100F/THA-120PC

| | |
|--------------------------|---|
| Aluminum profile frames: | 25 mm |
| Case handles: | 2 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Accessory compartment: | 10 cm x 33 cm x 38 cm |
| Compartment dimensions: | 28,5 cm x 33 cm x 38 cm |
| Inside dimensions: | 67 cm x 33 cm x 41,5 cm |
| Dimensions: | Width: 76 cm Depth: 37 cm Height: 53 cm |
| Weight: | 13,60 kg |